


AMP SMA, UMCC

TE Internal #: 2032440-1 UMCC to SMA Bulkhead Cable Assembly, .66 ft [.2 m], Black Cable, 0 – 9 GHz Operating Frequency, 50 Ω, FEP, .054 in [1.37 mm] Diameter, UMCC Plug

View on TE.com >

Cable Assemblies > RF Cable Assemblies



Connector Type (End A): UMCC Plug

Jacket Material: FEP

Cable Assembly Length: .2 m [.66 ft]

Cable Color: Black

Operating Temperature Range: -40 – 90 °C [-40 – 194 °F]

Features



Product Type Features

Coax Cable Type	1.37mm Coax			
Connector Type (End A)	UMCC Plug			
Connector Type (End B)	SMA Bulkhead Plug			
Cable Assembly Type	UMCC to SMA Bulkhead			
Configuration Features				
Number of Connectorized Ends	2			
Electrical Characteristics				
Insulation Resistance	50 MΩ			
Operating Voltage	60 VAC			
Impedance	50 Ω			
Signal Characteristics				
Velocity of Propagation	70%			
Body Features				

UMCC to SMA Bulkhead Cable Assembly, .66 ft [.2 m], Black Cable, 0 – 9 GHz Operating Frequency, 50 Ω , FEP, .054 in [1.37 mm] Diameter, UMCC Plug



Conductor Plating Material	Silver			
Shield Plating Material	Silver			
Shield Material	Copper			
Conductor Material	Copper			
Strain Relief Type	HST			
Jacket Material	FEP			
Cable Color	Black			
Contact Features				
Center Contact Plating	Gold			
Contact Base Material	Brass, Phosphor Bronze			
Mechanical Attachment				
Mating Diameter	2 mm			
Dimensions				
Mated Height	2.5 mm			
Outside Cable Diameter	1.37 mm[.054 in]			
Usage Conditions				
Operating Temperature Range	-40 - 90 °C[-40 - 194 °F]			

Operation/Application

Shielded	Yes
Operating Frequency	0 – 9 GHz
Other	
Dielectric Material	FEP
Cable Assembly Length	.2 m[.66 ft]
Product Compliance	
Product Compliance For compliance documentation, visit the product page on TE.com>	
For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	Compliant
For compliance documentation, visit the product page on TE.com>	Compliant Compliant
For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	

UMCC to SMA Bulkhead Cable Assembly, .66 ft [.2 m], Black Cable, 0 – 9 GHz Operating Frequency, 50 Ω , FEP, .054 in [1.37 mm] Diameter, UMCC Plug



Does not contain REACH SVHC

Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free

Not reviewed for solder process capability


Halogen Content

Solder Process Capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




UMCC to SMA Bulkhead Cable Assembly, .66 ft [.2 m], Black Cable, 0 – 9 GHz Operating Frequency, 50 Ω , FEP, .054 in [1.37 mm] Diameter, UMCC Plug






Also in the Series | AMP SMA



Rack & Panel Ferrules & Inserts(1)	RF Cable Assemblies(2)	RF Connector Hardware(2)	RF Connector Launchers(8)




Also in the Series UMCC

UMCC to SMA Bulkhead Cable Assembly, .66 ft [.2 m], Black Cable, 0 – 9 GHz Operating Frequency, 50 Ω, FEP, .054 in [1.37 mm] Diameter, UMCC Plug





Customers Also Bought



RJ45 W LED 2X2,30u'',DIP,H=25.4mm	DIAMOND GRIP 12-10 HT R 10	2MMFB,IS,ASY,024,SIG,HDR,SL	PROCRIMPER TOOL & DIE
000 AAAA 000	 		
TE Part #58525-2 PROCRIMPER DIE	TE Part #728038-000 301A511-125-0		

Documents

Product Drawings

C/A, UMCC TO SMA BHD JACK, 1.37MM L200MM

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2032440-1_A.2d_dxf.zip

UMCC to SMA Bulkhead Cable Assembly, .66 ft [.2 m], Black Cable, 0 – 9 GHz Operating Frequency, 50 Ω , FEP, .054 in [1.37 mm] Diameter, UMCC Plug



English

Customer View Model ENG_CVM_CVM_2032440-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2032440-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

UMCC - Ultraminiature Coax Connector & Cable Assembly Series Datasheet 1-1773441-5

English

UMCC Ultraminiature Coax Connector and Cable Assembly Series

English

Product Environmental Compliance TE Material Declaration

English