# NC machine reamer HSSE with straight shank For universal use up to 1000 $\mbox{N/mm}^{2}$



## Application

for cutting H7 fit tolerances in through holes and blind holes on NC machines or conventional machines up to 1000  $\rm N/mm^2.$ 

 $\blacksquare$  7-8° left-hand spiral, type D, with centring hole and offset shank

■ good bore hole quality (dimensional tolerance, roundness, surface quality)

Application	Steel (N/mm²)		Stainless steel		Alu		Brass					Graphite		Titan-			Hard mat.		
	<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long	tics	G(C)FK	GjMW	alloy	alloy	alloy	<55 HRC	<65 HRC
	12	9	7	8	7	17	17	17	17	13	13	13		11	5	5	5		

Art. No.	11628 100				
Cutting material	HSSE				
Tolerance of fit	H7				
Groove type	Left-hand twist, 7-8°				
Tool holding device	HA parallel shank				
Cutting edge diameter	10 mm				
Length	133 mm				
Cutting edge length	38 mm				
Projecting length	93 mm				
Shaft diameter	10 mm				
Number of cutting edges	6 PCS				
Surface	Uncoated				
f steel 1000	0.15 mm/U				
DIN	212				

### **EAN-Code**

4050293006148

