SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

DOW CORNING

## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 14.12.2016
1.8	24.04.2017	675277-00009	Date of first issue: 27.10.2014

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifier				
	Trade name	:	DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR		
	Product code	:	0000000003279111		
1.2	Relevant identified uses of th	e s	substance or mixture and uses advised against		
	Use of the Sub- stance/Mixture	:	Adhesive, binding agents		
1.3	Details of the supplier of the	saf	fety data sheet		
	Company	:	Dow Corning Europe S.A. rue Jules Bordet - Parc Industriel - Zone C B-7180 Seneffe		
	PO box	:	65091		
	Telephone	:	English Tel: +49 611237507 Deutsch Tel: +49 611237500 Français Tel: +32 64511149 Italiano Tel: +32 64511170 Español Tel: +32 64511163		
	E-mail address of person responsible for the SDS	:	sdseu@dowcorning.com		

1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350 Dow Corning (Wiesbaden 24h) Tél: +49 61122158 Dow Corning (Seneffe 24h) Tel: +32 64 888240

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### Additional Labelling

EUH210 Safety data sheet available on request.



Version	Revision Date: 24.04.2017	SDS Number:	Date of last issue: 14.12.2016
1.8		675277-00009	Date of first issue: 27.10.2014

EUH208 Contains 4,5-Dichloro-2-N-Octyl-4-Isothiazolin-3-One. May produce an allergic reaction.

#### 2.3 Other hazards

None known.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Silicone elastomer

#### Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
Octamethylcyclotetrasiloxane	556-67-2	Flam. Liq. 3; H226	>= 0.25 - < 1
	209-136-7	Repr. 2; H361f	
	014-018-00-1	Aquatic Chronic 4;	
	01-2119529238-36	H413	
4,5-Dichloro-2-N-Octyl-4-	64359-81-5	Acute Tox. 4; H302	>= 0.0025 - <
Isothiazolin-3-One	264-843-8	Acute Tox. 2; H330	0.025
		Acute Tox. 4; H312	
		Skin Corr. 1C; H314	
		Eye Dam. 1; H318	
		Skin Sens. 1A; H317	
		Aquatic Acute 1;	
		H400	
		Aquatic Chronic 1;	
		H410	

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice	:	In the case of accident or if you feel unwell, seek medical ad- vice immediately. When symptoms persist or in all cases of doubt seek medical advice.
Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
If inhaled	:	If inhaled, remove to fresh air. Get medical attention.
In case of skin contact	:	In case of contact, immediately flush skin with soap and plenty of water.

DOW CORNING

## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version 1.8	Revision Date: 24.04.2017	SDS Number: 675277-00009	Date of last issue: 14.12.2016 Date of first issue: 27.10.2014
		Get medical Wash clothin	taminated clothing and shoes. attention. Ig before reuse. clean shoes before reuse.
In case of eye contact		•	vith water as a precaution. attention if irritation develops and persists.
If swallowed		Get medical	, DO NOT induce vomiting. attention. thoroughly with water.

**4.2 Most important symptoms and effects, both acute and delayed** None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	t
-----------	---

: Treat symptomatically and supportively.

#### **SECTION 5: Firefighting measures**

5.1	Extinguishing media		
	Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
	Unsuitable extinguishing media	:	None known.
5.2	Special hazards arising from	the	substance or mixture
	Specific hazards during fire- fighting	:	Exposure to combustion products may be a hazard to health.
	Hazardous combustion prod- ucts	:	Carbon oxides Silicon oxides Formaldehyde
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
	Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so.

Evacuate area.

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

	Version 1.8	Revision Date: 24.04.2017	SDS Number: 675277-00009	Date of last issue: 14.12.2016 Date of first issue: 27.10.2014
--	----------------	---------------------------	-----------------------------	---

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, prote	ctive equipment and emergency procedures
Personal precautions	: Use personal protective equipment. Follow safe handling advice and personal protective equip- ment recommendations.
6.2 Environmental precautions	
Environmental precautions	: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
6.3 Methods and material for co	ontainment and cleaning up
Methods for cleaning up	: Soak up with inert absorbent material. For large spills, provide dyking or other appropriate contain- ment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container

 ds for cleaning up
 Soak up with inert absorbent material. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

#### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	:	Use only with adequate ventilation.
Advice on safe handling	:	Do not swallow. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Take care to prevent spills, waste and minimize release to the environment.
Hygiene measures	:	Ensure that eye flushing systems and safety showers are



Version 1.8	Revision Date: 24.04.2017		DS Number: 75277-00009	Date of last issue: 14.12.2016 Date of first issue: 27.10.2014
				he working place. When using do not eat, Vash contaminated clothing before re-use.
7.2 Conditions for safe storage, including any incompatibilities				
Requirements for storage areas and containers		:	Keep in properly the particular nati	labelled containers. Store in accordance with ional regulations.
Advice on common storage		:	Do not store with the following product types: Strong oxidizing agents	
7.3 Spec	ific end use(s)			
•	cific use(s)	:		ns are for room temperature handling. Use at ature or aerosol/spray applications may re- autions.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis					
Amorphous fumed	112945-52-	TWA (inhalable	6 mg/m3	GB EH40					
silica	5	dust)	(Silica)	OD EI 140					
Further information	-			duat are these					
Further mormation	For the purposes of these limits, respirable dust and inhalable dust are the fractions of airborne dust which will be collected when sampling is undertaken the sampling is undertaken as a set of the sampling is a set of the set o								
			escribed in MDHS14/3 Gene						
			of respirable and inhalable of						
			hazardous to health includes						
			ion in air equal to or greater						
	8-hour TWA c	f inhalable dust or 4	mg.m-3 8-hour TWA of resp	irable dust.					
	This means th	at any dust will be s	ubject to COSHH if people a	re exposed					
	above these le	evels. Some dusts ha	ave been assigned specific V	VELs and ex-					
	posure to thes	se must comply with	the appropriate limit., Most in	ndustrial dusts					
	contain particl	contain particles of a wide range of sizes. The behaviour, deposition and fate							
		of any particular particle after entry into the human respiratory system and the							
			nd on the nature and size of						
		HSE distinguishes two size fractions for limit-setting purposes termed 'inhala-							
	ble' and 'respirable'., Inhalable dust approximates to the fraction of airborne								
		material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates							
			e gas exchange region of th						
			al are given in MDHS14/3., V						
			ir own assigned WEL, all the						
	should be complied with., Where no specific short-term exposure limit is listed,								
	a figure three		exposure should be used						
		TWA (Respirable	2.4 mg/m3	GB EH40					
		dust)	(Silica)						
Further information	For the purpo	ses of these limits, re	espirable dust and inhalable	dust are those					

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version 1.8	Revision Date: 24.04.2017			Date of last issue: 14.12.2016 Date of first issue: 27.10.2014	
	in ac samp COS kind 8-hou This abov posu conta of an body HSE ble' a mate availa to the defin conta shou a figu	cordance ling and g HH definit when pres in TWA of means that the these le re to these in particle y particula response distinguis nd 'respir rial that en able for de fraction f tions and in compo d be com	with the methods gravimetric analys tion of a substanc sent at a concentr f inhalable dust or at any dust will be evels. Some dusts e must comply will es of a wide range ar particle after en that it elicits, dep shes two size fract rable'., Inhalable d nters the nose an eposition in the re that penetrates to a explanatory mate onents that have the polied with., Where times the long-term	will be collected when sampling described in MDHS14/3 Gener- is of respirable and inhalable d e hazardous to health includes ation in air equal to or greater t 4 mg.m-3 8-hour TWA of respi- subject to COSHH if people an have been assigned specific V h the appropriate limit., Most in of sizes. The behaviour, depo- try into the human respiratory s end on the nature and size of t ions for limit-setting purposes t ust approximates to the fraction d mouth during breathing and is spiratory tract. Respirable dust the gas exchange region of the rial are given in MDHS14/3., W heir own assigned WEL, all the an ospecific short-term exposu- n exposure should be used	ral methods for lust, The dust of any than 10 mg.m-3 irable dust. re exposed VELs and ex- ndustrial dusts sition and fate system and the the particle. termed 'inhala- n of airborne s therefore approximates e lung. Fuller Vhere dusts relevant limits ire limit is listed,
	nethylcyclo- 556-6 iloxane	57-2	TWA	10 ppm	US WEEL

## These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Amorphous fumed silica

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
Octamethylcyclotetra- siloxane	Workers	Inhalation	Acute systemic ef- fects	73 mg/m3
	Workers	Inhalation	Acute local effects	73 mg/m3
	Workers	Inhalation	Long-term systemic effects	73 mg/m3
	Workers	Inhalation	Long-term local ef- fects	73 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	13 mg/m3
	Consumers	Inhalation	Acute local effects	13 mg/m3
	Consumers	Inhalation	Long-term systemic effects	13 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	13 mg/m3
	Consumers	Ingestion	Acute systemic ef- fects	3.7 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	3.7 mg/kg bw/day

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
----------------	---------------------------	-------

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 14.12.2016
1.8	24.04.2017	675277-00009	Date of first issue: 27.10.2014

Octamethylcyclotetrasiloxane	Fresh water	0.00044 mg/l
	Marine water	0.000044 mg/l
	Fresh water sediment	0.64 mg/kg
	Marine sediment	0.064 mg/kg
	Soil	0.13 mg/kg
	Sewage treatment plant	> 10 mg/l
4,5-Dichloro-2-N-Octyl-4- Isothiazolin-3-One	Fresh water	0.034 µg/l
	Fresh water sediment	0.41 mg/kg
	Marine sediment	0.0034 mg/kg
	Sewage treatment plant	0.064 mg/l
	Soil	0.062 mg/kg
	Oral (Secondary Poisoning)	4.49 mg/kg food
	Marine water	0.0068 µg/l

#### 8.2 Exposure controls

#### **Engineering measures**

Processing may form hazardous compounds (see section 10). Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

#### Personal protective equipment

Eye protection	:	Wear the following personal protective equipment: Safety glasses
Hand protection Material	:	Chemical-resistant gloves
Remarks	:	Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous sub- stance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
Skin and body protection	:	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Organic vapour type (A)

according to Regulation (EC) No. 1907/2006



# DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 14.12.2016
1.8	24.04.2017	675277-00009	Date of first issue: 27.10.2014

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance	:	paste
Colour	:	colourless
Odour	:	Acetic acid
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	> 100 °C Method: closed cup
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	No data available
Relative density	:	1.02
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	Not applicable
Explosive properties	:	Not explosive

DOW CORNING

## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version 1.8	Revision Date: 24.04.2017	SDS Number: 675277-00009	Date of last issue: 14.12.2016 Date of first issue: 27.10.2014
Oxidizi	ng properties	: The substand	ce or mixture is not classified as oxidizing.
9.2 Other in Molecu Self-ig	ular weight		lable e or mixture is not classified as pyrophoric. The mixture is not classified as self heating.

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Not classified as a reactivity hazard.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions	<ul> <li>Use at elevated temperatures may form highly hazardous compounds.</li> <li>Can react with strong oxidizing agents.</li> <li>Hazardous decomposition products will be formed at elevated temperatures.</li> </ul>
10.4 Conditions to avoid	

## Conditions to avoid : None known.

10.5 Incompatible materials	
-----------------------------	--

Materials to avoid	: Oxidizing	agents
--------------------	-------------	--------

#### **10.6 Hazardous decomposition products**

Thermal decomposition	:	Formaldehyde
-----------------------	---	--------------

#### **SECTION 11: Toxicological information**

11.1	Information on toxicological ef	fects
	Information on likely routes of : exposure	Skin contact Ingestion Eye contact
	Acute toxicity Not classified based on available	information.
	Components:	
	Octamethylcyclotetrasiloxane:	
	Acute oral toxicity :	LD50 (Rat): > 4,800 mg/kg

**SAFETY DATA SHEET** according to Regulation (EC) No. 1907/2006

DOW CORNING

## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version 1.8	Revision Date: 24.04.2017		OS Number: 5277-00009	Date of last issue: 14.12.2016 Date of first issue: 27.10.2014
			Assessment: The icity Remarks: On bas	substance or mixture has no acute oral tox-
Acu	te inhalation toxicity	:	LC50 (Rat): 2975 Exposure time: 4 Test atmosphere: Assessment: The tion toxicity Remarks: On bas	h vapour substance or mixture has no acute inhala-
Acu	te dermal toxicity	:	LD50 (Rabbit): > Assessment: The toxicity Remarks: On bas	substance or mixture has no acute dermal
4.5-	Dichloro-2-N-Octyl-4-Is	othia	azolin-3-One:	
	te oral toxicity	:	LD50 (Rat): 1,636	∂ mg/kg
Acu	te inhalation toxicity	:	LC50 (Rat): 0.26 Exposure time: 4 Test atmosphere: Assessment: Corr	h
Acu	te dermal toxicity	:	Acute toxicity esti Method: Expert ju	mate: 1,100 mg/kg idgement
Not	n corrosion/irritation classified based on avail	able	information.	
<u>Cor</u>	nponents:			
Spe Res	amethylcyclotetrasiloxa ecies: Rabbit sult: No skin irritation narks: On basis of test da			
	Dichloro-2-N-Octyl-4-Iso sult: Corrosive after 1 to 4			

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

#### Octamethylcyclotetrasiloxane:

Species: Rabbit Result: No eye irritation Remarks: On basis of test data.

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 14.12.2016
1.8	24.04.2017	675277-00009	Date of first issue: 27.10.2014

#### 4,5-Dichloro-2-N-Octyl-4-Isothiazolin-3-One:

Result: Irreversible effects on the eye Remarks: Based on skin corrosivity.

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### Product:

Assessment: Does not cause skin sensitisation.

Test Type: Buehler Test Result: negative Remarks: On basis of test data.

#### **Components:**

#### Octamethylcyclotetrasiloxane:

Assessment: Does not cause skin sensitisation.

Test Type: Maximisation Test Species: Guinea pig Result: negative Remarks: On basis of test data.

#### 4,5-Dichloro-2-N-Octyl-4-Isothiazolin-3-One:

Test Type: Maximisation Test Exposure routes: Skin contact Species: Guinea pig Result: positive

Assessment: Probability or evidence of high skin sensitisation rate in humans

#### Germ cell mutagenicity

Not classified based on available information.

#### Components:

#### Octamethylcyclotetrasiloxane:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: On basis of test data.
	:	Test Type: Mutagenicity (in vitro mammalian cytogenetic test) Result: negative Remarks: On basis of test data.

according to Regulation (EC) No. 1907/2006

DOW CORNING

## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Vers 1.8	ion	Revision Date: 24.04.2017	-	0S Number: 5277-00009	Date of last issue: 14.12.2016 Date of first issue: 27.10.2014
			:	Test Type: Chrom Result: negative Remarks: On bas	nosome aberration test in vitro is of test data.
			:	Test Type: In vitro malian cells Result: negative Remarks: On bas	o sister chromatid exchange assay in mam- is of test data.
			:	Test Type: DNA c thesis in mammal Result: negative Remarks: On bas	
	Genoto	oxicity in vivo	:	cytogenetic assay Species: Rat	: inhalation (vapour)
				Test Type: Roder Species: Rat Application Route Result: negative Remarks: On bas	
	Germ o sessme		:	Animal testing dic	not show any mutagenic effects.
		<b>ogenicity</b> ssified based on availa	able	information.	
	•	ductive toxicity			
		ssified based on availa	able	information.	
		onents:			
		ethylcyclotetrasiloxa on fertility	ne:	Test Type: Two-a	eneration reproduction toxicity study
				Species: Rat, ma	e and female : inhalation (vapour) is on fertility
	Effects ment	on foetal develop-	:	Species: Rabbit Application Route	tal development toxicity study (teratogenicity) :: inhalation (vapour) fects on foetal development is of test data.
	Reprod sessme	luctive toxicity - As- ent	:		f adverse effects on sexual function and animal experiments.
				10/10	

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 14.12.2016
1.8	24.04.2017	675277-00009	Date of first issue: 27.10.2014

#### 4,5-Dichloro-2-N-Octyl-4-Isothiazolin-3-One:

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
Effects on foetal develop- ment	:	Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Components:

#### Octamethylcyclotetrasiloxane:

Exposure routes: Ingestion Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Exposure routes: inhalation (vapour) Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Exposure routes: Skin contact Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

#### 4,5-Dichloro-2-N-Octyl-4-Isothiazolin-3-One:

Exposure routes: Ingestion Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

#### Repeated dose toxicity

#### Components:

#### Octamethylcyclotetrasiloxane:

Species: Rat Application Route: Ingestion Remarks: On basis of test data.

Species: Rat Application Route: inhalation (vapour) Remarks: On basis of test data.



Version	Revision Date:	SDS Number:	Date of last issue: 14.12.2016
1.8	24.04.2017	675277-00009	Date of first issue: 27.10.2014

Species: Rabbit Application Route: Skin contact Remarks: On basis of test data.

#### 4,5-Dichloro-2-N-Octyl-4-Isothiazolin-3-One:

Species: Rat NOAEL: 20 mg/kg LOAEL: 100 mg/kg Application Route: Ingestion Exposure time: 28 Days

#### Aspiration toxicity

Not classified based on available information.

#### **Further information**

#### **Components:**

#### Octamethylcyclotetrasiloxane:

Remarks: Results from a 2 year repeated vapour inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Components:

#### Octamethylcyclotetrasiloxane:

Toxicity to fish	:	LC50 (Cyprinodon variegatus (sheepshead minnow)): > 0.0063 mg/l Exposure time: 336 h Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Mysidopsis bahia (opossum shrimp)): > 0.0091 mg/l Exposure time: 96 h Remarks: No toxicity at the limit of solubility
Toxicity to algae	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.022 mg/l Exposure time: 72 h Remarks: No toxicity at the limit of solubility
Toxicity to fish (Chronic tox- icity)	:	NOEC: >= 0.0044 mg/l Species: Oncorhynchus mykiss (rainbow trout) Remarks: On basis of test data.

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Versi 1.8	ion	Revision Date: 24.04.2017	-	9S Number: 5277-00009	Date of last issue: 14.12.2016 Date of first issue: 27.10.2014
				No toxicity at the I	imit of solubility
;		to daphnia and other invertebrates (Chron- ty)	:	NOEC: >= 0.0079 Exposure time: 21 Species: Daphnia Remarks: On bas No toxicity at the I	l d magna (Water flea) is of test data.
	Ecotox	icology Assessment			
	Chronic	aquatic toxicity	:	May cause long la	asting harmful effects to aquatic life.
	4,5-Dic	hloro-2-N-Octyl-4-Iso	thia	zolin-3-One:	
	Toxicity	r to fish	:	LC50 (Oncorhync Exposure time: 96	hus mykiss (rainbow trout)): 0.0027 mg/l ን h
		to daphnia and other invertebrates	:	EC50 (Daphnia m Exposure time: 48	agna (Water flea)): 0.0052 mg/l 3 h
	Toxicity	to algae	:	ErC50 (Pseudokir mg/l Exposure time: 72 Method: OECD Te	
	M-Facto icity)	or (Acute aquatic tox-	:	100	
	Toxicity	to microorganisms	:	EC50 : > 5.7 mg/l Exposure time: 3	
	Toxicity icity)	to fish (Chronic tox-	:	NOEC: 0.00056 n Exposure time: 97 Species: Oncorhy	
;		to daphnia and other invertebrates (Chron- ty)	:	NOEC: 0.00063 n Exposure time: 21 Species: Daphnia	
	M-Facto toxicity)	or (Chronic aquatic	:	10	
12.2	Persist	ence and degradabil	ity		
	Compo	onents:			
	Octame	ethylcyclotetrasiloxa	ne:		
	Biodegr	radability	:	Result: Not readily Biodegradation: 3 Exposure time: 28 Method: OECD Te	3.7 % 3 d
:	Stability	in water	:	Degradation half I	ife: 69.3 - 144 h (24.6 °C)
				15 / 10	

according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version 1.8	Revision Date: 24.04.2017		8 Number: 277-00009	Date of last issue: 14.12.2016 Date of first issue: 27.10.2014			
	pH: 7Method: OECD Test Guideline 111						
4,5-	Dichloro-2-N-Octyl-4-Is	othiaz	olin-3-One:				
Biod	Biodegradability : Result: rapidly degradable						
12.3 Bio	12.3 Bioaccumulative potential						
<u>Cor</u>	Components:						
Oct	amethylcyclotetrasilox	ane:					
Bioa	accumulation		Species: Pimephales promelas (fathead minnow) Bioconcentration factor (BCF): 12,400				
	tition coefficient: n- anol/water	:	log Pow: 6.48 (25.1 °C)				
4,5-	4,5-Dichloro-2-N-Octyl-4-Isothiazolin-3-One:						
Bioa	accumulation		Species: Lepomis macrochirus (Bluegill sunfish) Bioconcentration factor (BCF): 750				
	tition coefficient: n- anol/water	:	log Pow: 2.8				
	12.4 Mobility in soil						
	data available						
	12.5 Results of PBT and vPvB assessment						
<u>Cor</u>	nponents:						
Oct	Octamethylcyclotetrasiloxane:						
Ass	essment	   	rent REACh Anne D4 has been ass However, D4 doe substances. The	ethylcyclotetrasiloxane (D4) meets the cur- ex XIII criteria for PBT and vPvB. In Canada, essed and deemed to meet the PiT criteria. es not behave similarly to known PBT/vPvB weight of scientific evidence from field stud- 4 is not biomagnifying in aquatic and terres-			

substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

#### 12.6 Other adverse effects

No data available

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

**DOW CORNING** 

## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version 1.8	Revision Date: 24.04.2017	SDS Number: 675277-00009	Date of last issue: 14.12.2016 Date of first issue: 27.10.2014		
Product		According to the are not product s Waste codes sh	Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.		
Conta	aminated packaging	dling site for rec	s should be taken to an approved waste han- ycling or disposal. specified: Dispose of as unused product.		

#### **SECTION 14: Transport information**

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

Remarks

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Dimethylbis[(1- oxoneodecyl)oxy]stannane (20)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EC) No 850/2004 on persistent organic pol- lutants	:	Not applicable
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import	:	Not applicable



Version	Revision Date:	SDS Number:	Date of last issue: 14.12.2016
1.8	24.04.2017	675277-00009	Date of first issue: 27.10.2014

of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

#### The components of this product are reported in the following inventories:

REACH

: For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.

#### **15.2 Chemical safety assessment**

A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 :	Flammable liquid and vapour.
H302 :	Harmful if swallowed.
H312 :	Harmful in contact with skin.
H314 :	Causes severe skin burns and eye damage.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.
H330 :	Fatal if inhaled.
H361f :	Suspected of damaging fertility.
H400 :	Very toxic to aquatic life.
H410 :	Very toxic to aquatic life with long lasting effects.
H413 :	May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Acute aquatic toxicity
Aquatic Chronic	:	Chronic aquatic toxicity
Eye Dam.	:	Serious eye damage
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Corr.	:	Skin corrosion
Skin Sens.	:	Skin sensitisation
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
US WEEL / TWA	:	Time weighted average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regula-

#### SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006



## DOW CORNING(R) 785 SANITARY ACETOXY SILICONE CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 14.12.2016
1.8	24.04.2017	675277-00009	Date of first issue: 27.10.2014

tion; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified: NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations: vPvB - Very Persistent and Very Bioaccumulative

#### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN