Product data sheet Characteristics

ZBZ1600

Padlockable guard for mushroom head Ø40, metal, chromium plated





Main	
Range of product	Harmony XB4 Harmony XB5
Product or component type	Guard
Accessory / separate part category	Isolation accessory
Product compatibility	ZB5AS9. XB5AS8. XB4BS8. XB5AS9. ZB5AS8. XB4BT8. ZB4BS8. ZB4BT8. ZB5AT8. ZB5AT8. ZB4BS9. XB4BS9. XB5AT8.
Accessory / separate part destination	Ø 40 mm emergency stop push-button For standard head
Color	Chromium plated
Quantity per set	Set of 1

Complementary

Material	Metal
Net Weight	0.10 lb(US) (0.046 kg)

Ordering and shipping details

Category	22469 - PUSHBUTTON,22MM ACCESSORIES-NEW
Discount Schedule	CS2
GTIN	00785901810193
Nbr. of units in pkg.	1
Package weight(Lbs)	0.13 lb(US) (0.06 kg)
Returnability	Yes
Country of origin	FR

Packing Units

r doking office	
Unit Type of Package 1	PCE
Package 1 Height	1.73 in (4.4 cm)
Package 1 width	2.09 in (5.3 cm)
Package 1 Length	2.13 in (5.4 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	10.09 oz (286 g)
Package 2 Height	1.73 in (4.4 cm)
Package 2 width	2.13 in (5.4 cm)
Package 2 Length	10.43 in (26.5 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	160
Package 3 Weight	22.04 lb(US) (9.997 kg)

Package 3 Height	11.81 in (30 cm)		
Package 3 width	11.81 in (30 cm)		
Package 3 Length	15.75 in (40 cm)		
Offer Sustainability			
Sustainable offer status	Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
REACh Regulation	☑ REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration		
Toxic heavy metal free	Yes		
Mercury free	Yes		
RoHS exemption information	₫Yes		
China RoHS Regulation	China RoHS Declaration		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	End Of Life Information		

Contractual warranty

Warranty	18 months	