

PRODUCT DESCRIPTION

To provide a single solution for the professional, Tempo has developed the 711K Professional Tone and Probe Kit combining the 77GX Tone Generator and 200GX Inductive Amplifier in a rugged carrying case. The new GX series incorporates many user-requested features resulting in an easy to use product we are proud to call Tempo. The only thing missing is complexity.

77GX Tone Generator

The 77GX Tone Generator incorporates a host of user-requested features including microprocessor controlled circuitry for increased reliability, three selectable tone outputs for multiple line identification, two-line polarity indication for fast outlet checks, selectable power outputs for use on open or shorted pairs, continuity testing and automatic shut-off to prevent battery drain.

200GX Inductive Amplifier

The new 200GX Inductive Amplifier features a simple, one button operation and comfortable, ergonomic design. The adjustable volume control, LED visual signal strength indication and powerful speaker make the 200GX ideal for noisy environments. Additionally, the 200GX offers recessed connectors for use with telephone test sets.



FEATURES

- Fast, Accurate Wire Identification
- Sends Tone to Identify Wires
- Three Distinct Tone Signatures
- High & Low power output settings
- Polarity Indication
- Continuity Test
- Talk Battery supply
- Adjustable Volume Control
- Visual Signal Strength Indication
- Large Speaker for Noisy Environments
- Facility for Headset/Buttset connection
- Choice of Metallic or Plastic Probe Tip
- Detachable 2-Line Modular Test Lead
- 3-Colour LED identifies AC Ring Voltage
- Rugged Industrial Design

Both the 77GX and the 200GX can be purchased separately and are part of a series of Tone Generators and Probes designed to meet the price and performance requirements of the various trades involved in cable installation and maintenance. In addition to this series (detailed overleaf) Tempo supply a number of application specific designs including, Modular Breakout Tone Generator, LAN Toner with HUB Blink, Tone Test Set, Alarm Loop Verifier Tone Generator, Data Mate, AC and DC coupled 1kHz Tone Generator and associated probe.

711K Professional Tone and Probe Kit

SPECIFICATIONS

77GX Tone Generator

Electrical:

Output Voltage (Talk Battery into 600Ω): 5.5VDC
 Output Power (into 600Ω) High Power: +8 dBm
 Low Power: +1 dBm

Output Frequency (nominal):

Tone: alternating 874/984Hz ±1%
 Warbling:
 Slow: 2.5Hz
 Medium: 6Hz
 Fast: 13Hz

Voltage Protection (into a 600Ω Circuit): 60VDC
 Auto Shut-Off (in Tone mode): 4 hours

Power Source:

Battery: 1 x 9V
 Battery Life (nominal): 50 hours

Environment:

Operating Temperature: 0°C to 50°C (32°F to 122°F)
 Storage Temperature: -50°C to 75°C (-58°F to 167°F)

Physical:

Length: 101.6mm (4.0 inches)
 Width: 41.9mm (1.65 inches)
 Depth: 38.1mm (1.5 inches)
 Weight: 0.13kg (0.29lbs)

Warranty: One Year

200GX Inductive Amplifier

Electrical:

Gain: 30dB
 Input Impedance: 100MΩ
 Probe Tip Resistance (min): Plastic Tip 300Ω
 Frequency Range (approx): 500 – 5kHz

Power Source:

Battery: 1 x 9V
 Battery Life (nominal): 50 hours

Environment:

Operating Temperature: 0°C to 50°C (32°F to 122°F)
 Storage Temperature: -50°C to 75°C (-58°F to 167°F)
 Relative Humidity: 80%
 Elevation (max): 2000m (6500 feet)

Physical:

Length: 229mm (9.0 inches)
 Width: 48mm (1.875 inches)
 Depth: 35mm (1.375 inches)
 Weight: 0.13kg (0.29lbs)

Warranty: One Year

| 77 Series Tone Generators Features and Specification | Model Numbers | | |
|---|---------------|---------|----------|
| | 77HP | 77HP/6A | 77HP/6AC |
| Selectable Warble | ✓ | ✓ | ✓ |
| Continuity Testing | ✓ | ✓ | ✓ |
| Polarity Testing | ✓ | ✓ | ✓ |
| Talk Battery Supply | ✓ | ✓ | ✓ |
| 2-Line Modular Test Lead - RJ11 | ✓ | ✓ | ✓ |
| 3-Colour LED Ring Voltage | ✓ | ✓ | ✓ |
| Weather Resistant | ✓ | ✓ | ✓ |
| Croc Clips | ✓ | | |
| Alligator Clips | | ✓ | ✓ |
| Cloth Test Lead | | | ✓ |

| 200 Series Inductive Amplifiers Features and Specification | Model Numbers | | |
|---|---------------|-------|-------|
| | 200EP | 200GX | 200FP |
| Powerful 2 inch Speaker | ✓ | ✓ | |
| Powerful Rear Fire Speaker | | | ✓ |
| One Button Operation | ✓ | ✓ | ✓ |
| Adjustable Volume Control | ✓ | ✓ | ✓ |
| LED for Visual Signal Strength Indication | ✓ | ✓ | ✓ |
| Recessed Tabs for Test Telephone or Headset connection | ✓ | ✓ | ✓ |
| Speaker Bypass when using Recessed Tabs | | ✓ | |
| Noise Filtration | | | ✓ |
| Continuous ON Feature | | | ✓ |
| Five Minute Auto Shut OFF | | | ✓ |
| Low Battery Indicator | | | ✓ |

