



**RoHS
Compliant**



Specifications:

Terminal	: Brass, Tin Plated, 0.8t
Insulator Body	: PC, Black
Screw	: #6-32, Steel, Ni Plated
Operation Temperatures	: -40°C to +120°C
Rated Current	: 20A 300V
Insulation Withstands Volt	: 2,000V 1 Min.
Insulation Resistance	: 2,000MΩ at DC 500V
Wire Range	: 12 to 22 AWG
Screw Torque	: 12lb-in

Diagram



Dimensions : Millimetres (Inches)

Part Number Table

Description	A(mm)	B(mm)	Part Number
Terminal Block, Barrier, 2POS, 22-12AWG	36.2	28.7	MC24299
Terminal Block, Barrier, 3POS, 22-12AWG	45.7	38.2	MC24300
Terminal Block, Barrier, 5POS, 22-12AWG	64.7	57.2	MC24302
Terminal Block, Barrier, 6POS, 22-12AWG	74.2	66.7	MC24303
Terminal Block, Barrier, 8POS, 22-12AWG	93.2	85.7	MC24304
Terminal Block, Barrier, 10POS, 22-12AWG	112.2	104.7	MC24305
Terminal Block, Barrier, 16POS, 22-12AWG	169.2	161.7	MC24307
Terminal Block, Barrier, 20POS, 22-12AWG	207.2	199.7	MC24308

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro