


Insulating Tapes

General Purpose PVC Tapes

multicomp PRO



General Purpose PVC Tapes

General purpose non-migratory plasticized insulation tape supplied in widths of 19mm and 38mm with all colours as detailed

Nominal Thickness : 0.15 mm
 Operating Temperature : 0°C to +80°C
 Dielectric Breakdown : 40 kV / mm
 Elongation : 170%

PVC insulating tape conforming to BS3924 and IEC454

Specification Table

| Colours | Roll Size | Part Number |
|---|-----------------|-------------------|
| Yellow | 19mm × 20m | PVC TAPE 1920Y |
| Blue | | PVC TAPE 1920BL |
| Green | | PVC TAPE 1920GR |
| White | | PVC TAPE 1920W |
| Grey | | PVC TAPE 1920GY |
| Brown | | PVC TAPE 1920BR |
| Yellow / Green | | PVC TAPE 1920YG |
| Red | | 19mm × 33m |
| Yellow | PVC TAPE 1933Y | |
| Blue | PVC TAPE 1933BL | |
| Green | PVC TAPE 1933GR | |
| White | PVC TAPE 1933W | |
| Grey | PVC TAPE 1933GY | |
| Brown | PVC TAPE 1933BR | |
| Yellow / Green | PVC TAPE 1933YG | |
| Black | 38mm × 20m | PVC TAPE 3820B |
| Black, Red, White, Yellow, Blue, Brown, Green and Yellow / Green* | 19mm × 5m | PVC TAPE 1905BX24 |

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 Element14.com/multicomp-pro

multicomp PRO