Data Sheet

Within Series Adaptor 46_BNC-50-0-1/133_N

Description

T-adaptor, 3 jacks BNC jack (female) / BNC jack (female)

Interface standard Series BNC - IEC 61169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	4 GHz	
Mechanical Data		
Number of matings	500	
Weight	0.0125 kg	
Environmental Data		
Operating temperature	-65 °C to 165 °C	
2011/65/EU (RoHS)	compliant	
Material Data		
Interface - BNC jack (female)		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Interface - BNC jack (female)		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating

Related Documents

Catalogue drawing

Insulator

DCA-00013495

PFA / PTFE

Ordering Information

Single package

46_BNC-50-0-1/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

