



Item	Size (WxL)	
203000	75 x 125mm (3" x 5") with write-on panels, with zipper	
203005	100 x 150mm (4" x 6"), with write-on panels, with zipper	
203010	125 x 200mm (5" x 8"), with write-on panels, with zipper	
203015	150 x 200mm (6" x 8"), with write-on panels, with zipper	
203025	200 x 250mm (8" x 10"), with write-on panels, with zipper	
203030	250 x 350mm (10" x 14"), with write-on panels, with zipper	
203040	0 100 x 150mm (4" x 6"), with zipper	
203065	250 x 350mm (10" x 14"), with zipper	
Sold 100 per package		

"Packaging used within an EPA shall consist of dissipative or conductive materials for intimate contact." [EN 61340-5-3 Clause 5.2 Inside an EPA]

- A. These products are made of an antistatic polyethylene film that under normal working conditions doesn't generate triboelectric charges.
- B. The bags are tough, amine free, do not affect polycarbonate housings and do not cause corrosion.
- C. The product is transparent and tinted pink. Typical film thickness is 75 micron.
- D. Bags are hot foil printed in yellow with a descriptive text and ESD protective symbol per EN 61340-5-1.
- E. The zip in the bags uses a double tooth locked closure system for strength this is impulsive sealed into the bags. It is made from Polyethylene.
- F. Dissipative bags can be used as packaging for ESDS and non-ESD sensitive items in ESD protected areas e.g. passive components, screws. The antistatic properties are long lasting provided the film is stored in a cool dry place. Do not store outside and do not expose the film to heat or store in an overheated warehouse.

PHYSICAL PROPERTIES:			
Density		920kg/m <sup>3</sup> (ASTM D792)	
Thickness		75 micron	
Tensile Strength		>10-12mpa (BS 2782)	
	CD	>10-12mpa (BS 2782)	
Elongation	MD	>250-300% (BS 2782)	
	CD	>400-500% (BS 2782)	
Tear Resistance		>50N/mm Thickness (BS 2782)	
ELECTRICAL PROPERTIES:			
Inner Surface Resistance (50% RH)		$1 \times 10^5$ to < 1 x $10^{11}$ ohms (IEC 61340-2-3)	
Outer Surface Resistance (50% RH)		$1 \times 10^5$ to < $1 \times 10^{11}$ ohms (IEC 61340-2-3)	
Shelf Life		2 years	
CHEMICAL PROPERTIES:			
Antistatic Additive		Amine Free - Non-Corrosive and Polycarbonate Compliant	
RoHS 2 and REACH Compliant			

MD = Machine direction, CD = Cross direction

Unless otherwise noted, tolerance ±10% Specifications and procedures subject to change without notice.

## **Antistatic Pink Bags with Zipper**



DESCO EUROPE 2A DUNHAMS LANE, LETCHWORTH GARDEN CITY, HERTFORDSHIRE, SG6 1BE, UK PHONE: +44 (0) 1462 672005

E-MAIL: Service@DescoEurope.com, INTERNET: DescoEurope.com

Drawing Number 203000

**DATE:**December 2017

United Kingdom