

Small Signal Product

500mW High Speed SMD Switching Diode

FEATURES

- Designed for mounting on small surface
- Extremely thin/leadless package
- High mounting capability, strong surge with stand, high reliability
- Pb free and RoHS compliant
- Halogen free



1206

MECHANICAL DATA

- Case: 1206 standard package, molded plastic
- Terminal: Gold plated, solderable per MIL-STD-750, method 2026 guaranteed
- High temperature soldering guaranteed: 260°C/10s
- Polarity: Indicated by cathode band
- Weight: 0.010 g (approximately)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Power dissipation	P _D	500	mW
Non-repetitive peak reverse voltage	V _{RSM}	100	V
Repetitive peak reverse voltage	V _{RRM}	75	V
Repetitive peak forward current	I _{FRM}	300	mA
Mean forward current	I _O	150	mA
Non-repetitive peak forward surge current T _p = 1sec square waveform T _p = 8.3ms single half sine waveform	I _{FSM}	0.5 2.0	A
Thermal resistance form junction ambient (Note 1)	R _{θJA}	375	°C/W
Junction and storage temperature range	T _J , T _{STG}	- 55 to + 150	°C

PARAMETER	SYMBOL	MIN	MAX	UNIT
Reverse breakdown voltage (Note 2)	V _(BR)	75	-	V
Forward voltage I _F =100mA	V _F	-	1	V
Reverse leakage current V _R =20V V _R =75V	I _R	-	25	nA
		-	5	μA
Junction capacitance V _R =0, f=1.0MHz	C _J		4.0	pF
Reverse recovery time (Note 3)	t _{rr}		4	ns

Note: 1 Valid provided that electrodes are kept at ambient temperature

Note: 2 Test Condition : I_R=100μA

Note: 3 Test Condition : I_F=10mA, I_R=1mA, R_L=100Ω

Small Signal Product

RATINGS AND CHARACTERISTICS CURVES

($T_A=25^\circ\text{C}$ unless otherwise noted)

Fig. 1 Typical Forward Characteristics




Fig. 2 Reverse Current VS. Reverse Voltage




Fig. 3 Admissible Power Dissipation Curve




Fig. 4 Typical Junction Capacitance





Fig. 5 Forward Resistance VS. Forward Current



Small Signal Product


ORDERING INFORMATION					
PART NO.	MANUFACTURE CODE	PACKING CODE	GREEN COMPOUND CODE	PACKAGE	PACKING
TS4148	(Note)	RX	Suffix "G"	1206	5K / 7" Reel
		RA			10K / 13" Reel

Note: Manufacture special control, if empty means no special control requirement.

EXAMPLE					
PREFERRED P/N	PART NO.	MANUFACTURE CODE	PACKING CODE	GREEN COMPOUND	DESCRIPTION
TS4148 RXG	TS4148		RX	G	Green compound
TS4148-C0 RXG	TS4148	C0	RX	G	Green compound

Small Signal Product

DIMENSIONS



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	3.00	3.40	0.118	0.134
B	1.30	1.70	0.051	0.067
C	0.35	0.75	0.014	0.030
D	0.75	0.95	0.030	0.037

Small Signal Product**Notice**

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.