

Product characteristics

Inductive sensor

Metal thread M30 x 1.5

Connector

Sensing range 10 mm; [f] flush mountable

Electrical data

Electrical design

DC PNP

Operating voltage [V]

10...36 DC

Current consumption [mA]

15 (24 V)

Protection class

III

Reverse polarity protection

yes

Outputs

Output function

normally open

Voltage drop [V]

< 2.5

Current rating [mA]

100

Short-circuit protection

pulsed

Overload protection

yes

Switching frequency [Hz]

250

Range

Sensing range [mm]

10

Real sensing range (Sr) [mm]

10 ± 10 %

Operating distance [mm]

0...8.1

Accuracy / deviations

Correction factors

mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / Al approx. 0.4 / Cu approx. 0.3

Hysteresis [% of Sr]

3...20

Switch-point drift [% of Sr]

-10...10

Environment

Ambient temperature [°C]

-25...100

Protection

IP 67

Tests / approvals

EMC

EN 60947-5-2

EN 55011:

class B

MTTF [Years]

1853

Mechanical data

Mounting

flush mountable

Housing materials

stainless steel 316Ti / 1.4571; PBT

Weight [kg]

0.162


# II5863 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Electrical connection

Connection

M12 connector; Gold-plated contacts

## Wiring



Accessories

Accessories (included)

2 lock nuts

Remarks

Pack quantity

[piece]

1

ifm electronic gmbh • Friedrichstraße 1 • 45128 Essen — We reserve the right to make technical alterations without prior notice. — GB — II5863 — 06.03.2003