# multicomp PRO

# Correct of the second s

## **Specifications:**


Maximum Electric Current

Maximum Electrical Rating Insulation Material Insulation Color Terminal Material Nema Tab Wire Range Terminal Surface Treatment Thickness Termination Method

# RoHS Compliant

ıt	:	AWG	22	20	18	16		
		AMP	3	4	7	10		
ıg	:	75°C 300V Max. Vinyl Red Brass						
ent	: .	0.032" × 0.25" (0.8mm × 6.35mm) 22 to 16AWG (0.5 to 1.5mm <sup>2</sup> ) Tin Plated 0.4mm Crimp						

## Diagram



#### Dimensions : Millimetres

# Part Number Table

Description	Part Number
Terminal, Piggyback, 0.25", Crimp, Red	MC29476

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

