

swissbit®

Product Fact Sheet


USB Flash Drive
for Secure Boot on
Raspberry Pi

PU-50n DP Series
"Raspberry Edition"

8GB
USB 3.1 SuperSpeed, MLC

Date: July 28, 2021
Revision: 1.02

durabit™
"the better MLC"



Made in Germany

Product Fact Sheet

PU-50n DP Series



Product Summary

- **Capacities:** 8 GBytes
- **Form Factor:** 24.0 mm x 12.1 mm x 4.5 mm
- **Compliance:** USB 3.1 Gen 1 SuperSpeed specification compatible (backward compliance with USB 2.0/1.1)
- **Performance:**
 - Read performance: sequential read up to 100 MBytes/s, random read IOPS up to 2,200
 - Write performance: sequential write up to 25 MBytes/s, random write IOPS up to 600
- **Operating Temperature Range:**
 - Industrial: -40 °C to 85 °C
- **Storage Temperature Range:** -40 °C to 85 °C
- **Operating Voltage:** 5.0 V ± 10%
- **Data Retention:** 10 years @ life begin; 1 year @ life end

Product Features

- This **USB nano stick** can be used as an **authentication device** for the Swissbit Secure Boot on Raspberry Pi solution (requires also one microSD card PS-45u DP Raspberry Edition)
- The solution is **protecting** Raspberry Pi **boot loader** (works with Raspberry Pi 2, 3B+, CM3+ and 4)
- **Authentication** is performed during the Swissbit customized **pre-boot** phase to unlock access
- **Encrypting user data and boot code** with **AES 256bit** to protect licenses, know-how and IP
- The **boot image can be set as read-only** to prevent unauthorized modification
- Restricting the access to data on the card by various configurable security policies
 - **PIN** – check a PIN entered via keyboard
 - **USB** – check presence of a USB authentication device (requires an Swissbit USB PU-50n „Raspberry Edition“).
Note: USB policy is currently supported on Raspberry Pi 2, 3B+ and CM3+.
 - **NET** policy – check presence of an authentication server in the network (requires an additional RaspberryPi as a server)

Ordering Information

Product Type	Product Series	Capacity	Part Number	Usage
USB nano	PU-50n DP "Raspberry Edition"	8 GBytes	SFU3008GC1PE2T0-I-GE-020-RPo	Use as authentication dongle in "USB policy"
microSD	PS-45u DP "Raspberry Edition"	8 GBytes	SFSD8192N3PM1T0-I-GE-020-RPo	One microSD card (8GB or 32GB) is required
microSD	PS-45u DP "Raspberry Edition"	32 GBytes	SFSD032GN3PM1T0-I-HG-020-RPo	

SDK & documentation

The SDK and user documentation is available for download under www.swissbit.com/secure-boot-rpi

Why Swissbit?

Swissbit strives to create innovative technologies for future market opportunities utilizing a highly skilled in-house research and development team. Swissbit maintains a marketing edge by continuing to manufacture world-class high quality memory and security products and providing customers with both high value and low cost of ownership achieved through efficient processes and procedures.