

## OMNIMATE Signal - series RSV SL FLA 3.8/1

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



### Effective: the link between LED and front panel.

Floodlight indicators allow users to monitor the switching states without requiring a special design: optical plastic directs the light from standard LEDs around a bend into the connectors or through the front plate.

The fibre-optic elements are simply clipped behind the relevant 90° bend male connectors (90° outlet direction). Versions with different incoming light beam heights achieve maximum light efficiency for LEDs with different designs or heights.

The advantages compared to conventional solutions:

- No additional LED circuit board required behind the front panel
- No "long-legged" LEDs with separate mounting required
- Bent fibre-optic cable line for maximum light efficiency
- Uncomplicated front plate bore holes due to circular shape of outgoing light beam
- Easy to maintain correct clearance and creepage distance
- Can be partitioned for smaller pole numbers

The result: simplified manufacturing process, reduced costs and simplified design

### General ordering data

|              |  |
|--------------|--|
| Type         | SL FLA 3.8/1   |
| Order No.    | <a href="#">1580110000</a>   |
| Version      | PCB plug-in connector, Accessories, Flood-light display, No. of poles: 1 |
| GTIN (EAN)   | 4008190050740  |
| Qty.         | 100 pc(s).   |
| Product data |  |

**Datenblatt**

**OMNIMATE Signal - series RSV  
SL FLA 3.8/1**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technische Daten**

**Dimensions and weights**

Net weight 0.52 g

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC001284    | UNSPSC     | 30-21-18-01 |
| eClass 6.2 | 27-26-92-01 | eClass 7.1 | 27-44-92-02 |

**Notes**

Notes

**Approvals**

Approvals



ROHS Conform