
## Piloted non return valve HGL-3/8-B Part number: 530032

**FESTO** 





## **Data sheet**

Feature	Value
Type code	HGL
Maritime classification	See certificate
Valve function	Unlockable non-return function
Pneumatic connection 1	G3/8
Pneumatic connection 2	G3/8
Pilot air port 21	G1/4
Actuation type	Pneumatic
Type of mounting	With external thread Screw-in
Operating pressure	0.5 bar 10 bar
Pilot pressure	1 bar 10 bar
Ambient temperature	-10 °C 60 °C
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Mounting position	Any
Symbol	00991456
Standard flow rate 1->2 (6-0)	1500 l/min
Standard nominal flow rate 1->2 (6-5)	1100 l/min
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
Storage temperature	-10 °C 60 °C
Temperature of medium	-10 °C 60 °C
Pilot medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Nominal tightening torque	12.5 Nm
Tolerance for nominal tightening torque	± 10%
Product weight	62.9 g
Note on materials	RoHS-compliant Free of copper and PTFE
Seals material	NBR

Feature	Value
Hollow bolt material	Anodized Wrought aluminum alloy
Releasing ring material	POM
Non-return collar material	NBR
Swivel joint material	Die-cast zinc