


## DSH TNC 255 (941 300)


- Application-optimised and prewired spark-gap-based type 1 and type 2 combined lightning current and surge arrester
- Compact design due to space-saving spark gap technology with a width of only 1 module / pole
- Allows compact lightning equipotential bonding including protection of terminal equipment



Figure without obligation



Basic circuit diagram DSH TNC 255



Dimension drawing DSH TNC 255

Application-optimised and prewired combined lightning current and surge arrester for TN-C systems.

| Type  | DSH TNC 255   |
|---|---|
| Part No.  | 941 300   |
| SPD according to EN 61643-11 / IEC 61643-11                               | type 1 + type 2 / class I + class II                              |
| Energy coordination with terminal equipment ( $\leq 10$ m)                | type 1 + type 2 + type 3  |
| Nominal voltage (a.c.) ( $U_N$ )  | 230 / 400 V (50 / 60 Hz)  |
| Max. continuous operating voltage (a.c.) ( $U_C$ )                        | 255 V (50 / 60 Hz)  |
| Lightning impulse current (10/350 $\mu$ s) [L1+L2+L3-PEN] ( $I_{total}$ ) | 37.5 kA   |
| Specific energy [L1+L2+L3-PEN] (W/R)                                      | 352.00 kJ/ohms  |
| Lightning impulse current (10/350 $\mu$ s) [L-PEN] ( $I_{imp}$ )          | 12.5 kA   |
| Specific energy [L-PEN] (W/R)   | 39.06 kJ/ohms   |
| Nominal discharge current (8/20 $\mu$ s) [L-PEN]/[L1+L2+L3-PEN] ( $I_n$ ) | 12.5 / 37.5 kA  |
| Voltage protection level ( $U_P$ )  | $\leq 1.5$ kV   |
| Follow current extinguishing capability (a.c.) ( $I_n$ )                  | 25 kA <sub>rms</sub>  |
| Follow current limitation / Selectivity                                   | no tripping of a 32 A gG fuse up to 25 kA <sub>rms</sub> (prosp.) |
| Response time ( $t_A$ )   | $\leq 100$ ns   |
| Max. mains-side overcurrent protection                                    | 160 A gG  |
| Temporary overvoltage (TOV) [L-N] ( $U_T$ ) – Characteristic              | 440 V / 120 min. – withstand                                      |
| Operating temperature range ( $T_U$ )                                     | -40 °C ... +80 °C   |
| Operating state / fault indication  | green / red   |
| Number of ports   | 1   |
| Cross-sectional area (L1, L2, L3, PEN) (min.)                             | 1.5 mm <sup>2</sup> solid / flexible                              |
| Cross-sectional area (L1, L2, L3, PEN) (max.)                             | 35 mm <sup>2</sup> stranded / 25 mm <sup>2</sup> flexible         |
| For mounting on   | 35 mm DIN rails acc. to EN 60715                                  |
| Enclosure material  | thermoplastic, red, UL 94 V-0                                     |
| Place of installation   | indoor installation   |
| Degree of protection  | IP 20   |
| Capacity  | 4 module(s), DIN 43880  |
| Approvals   | KEMA, VDE, UL   |
| Weight  | 386 g   |
| Customs tariff number (Comb. Nomenclature EU)                             | 85363090  |
| GTIN  | 4013364133556   |
| PU  | 1 pc(s)   |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.