

VOLTCRAFT®

VOLTCRAFT® - TOP PERFORMANCE IN EVERY WAY

"For more than 25 years, our product range has been dynamically adapting to the constant changes in the industry. We commit to offering first-class quality to our customers while delivering an excellent cost-performance ratio. This philosophy remains the cornerstone of Voltcraft's success."

PL-125-T4 DIGITAL THERMOMETER



VERSION 10/14

Nº 1013036

Robust thermometer with soft rubber case for type K and type J thermo-elements. The large illuminated display and the function keys arranged on the sides enable an ergonomic usage. The integrated real-time clock the MIN/MAX/AVG values with time stamp can be read, so considerably easier for long-term monitoring. In addition to the included wire sensors (1 pc. per channel) al type K and J temperature sensors with miniature thermo-element plug can be connected.

FEATURES:

4 channels // For thermo elements type-K/J //
MAX/MIN/AVG with time stamp // Data hold for 18000
measurement values // USB interface //

EQUIPMENT:

Temperature display in °C, °F or K // Auto-power-off-
function // Difference measurement (T1-T2 or T3-T4).

PACKAGE CONTENTS:

PL-125-T4 // 4x type-K-wire sensor (-20 to +250 °C) //
3 Batteries (AAA) // USB cable // Voltsoft standard
software-CD // Operating instructions.

TECHNICAL DATA:

| | |
|--------------------------|--------------------------|
| Model: | 4 Channel |
| Temperature range: | Type K: -200 to +1372 °C |
| Type J: -210 to +1100 °C | 0.2 V - 500 V |
| Temperature resolution: | 0.1 °C |
| Basic accuracy: | ff(0.15% + 1 °C) |
| Sensor type: | K/J |
| Interface: | USB |
| Power supply: | 3 micro batteries (AAA) |
| Dimensions (W x H x L): | 62 x 28 x 162 mm |
| Weight: | 184 g |



Legal notice

This data sheet is published by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau (www.conrad.com).
All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval by the editor. Reprinting, also in part, is prohibited.
This data sheet represent the technical status at the time of printing.

© Copyright 2014 by Conrad Electronic SE

V3_1014_02/VTP