

<b>Product type designation</b>	<b>RUGGEDCOM REPN-PSP01</b> RUGGEDCOM RE Panels for MX5000RE power module 1
<b>Signal-Inputs/outputs</b>	
Product component / Signaling contact	Yes
<b>Design, dimensions and weight</b>	
Design	removable module
Net weight	1.5 kg
<b>Permitted ambient conditions</b>	
Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage</li> <li>• during transport</li> <li>• Note</li> </ul>	-40 ... +85 °C -40 ... +85 °C -40 ... +85 °C A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP30
<b>Accessories</b>	
<b>Further Information / Internet Links</b>	
Internet-Link	
<ul style="list-style-type: none"> <li>• to website: Industry Mall/RUGGEDCOM selector</li> <li>• to website: Siemens RUGGEDCOM</li> <li>• to website: Selector for cables and connectors</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx Download Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="http://ruggedcom-selector.automation.siemens.com">http://ruggedcom-selector.automation.siemens.com</a> <a href="http://siemens.com/ruggedcom">http://siemens.com/ruggedcom</a> <a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>last modified:</b>	08/21/2017