DIN RAIL POWER SUPPLY 24VDC 480WATT

STONTRONICS: DG-480-24

Features:

- Universal / Full Range Input
- Highly Reliable Design
- 100% Full Load Burn-in Test
- 3 Year Warranty





Description:

The TT Electronics range of Din Rail Power Supplies can be installed on either TS-35/7 or TS-35/18. Featuring wide ranging universal Input for many industrial application and come with a 3 year warranty as standard. This 480watt unit is offered in 24v and comes with built in active PFC.

Specification	
Part Number	DG-480-24
DC Output	24V
Rated Output Current	20A
Ripple & Noise	<240mV
Voltage ADJ Range	24-28V
Voltage Accuracy	+/-3%
Line Regulation	+/- 0.5%
Load Regulation	+/-1%
Set up Time	<3S@230Vac
Hold up Time	<20mS @ 230Vac input, Full load
Temperature Coefficient	+/-0.03%
Overshoot and Undershoot	<5%
Input Voltage Range	85Vac - 264Vac
Input Frequency	47Hz-63Hz
Efficiency	94%
AC Current (max.)	<3A/100Vac
Inrush Current (max.)	<20A/110Vac <40A/230Vac Cold start
Leakage Current	Input-output:<0.25mA
Over Load Protection	120% - 150% of rated current
Over Voltage Protection	29-33V, constant voltage, Auto recovery
Short Circuit	Long-term mode, auto recovery
Operating Temp. & Humidity	-25°C to 70°C / 20% to 90%
Storage Temp. & Humidity	-40°C to 85°C / 5% to 95%
Safety Standards	UL508, UL60950, EN60950
Withstand Voltage	Primary-Secondary:3.0KVac; <10mA Primary-PG:2.5KVac; <10mA Secondary-PG0:5KVac-20mA
Isolation Resistance	>100M ohms
EMC Emission	Compliance to EN55022, EN55024, FCC PART 15 Class B
EMC Immunity	Compliance to EN61000-4-2,3,4,5,6,8,11; heavy industry level
MTBF	>300,000 hours
Dimensions	50mm x 124mm x 127mm

STONTRONICS


DIN RAIL POWER SUPPLY 24VDC 480WATT





0

STONTRONICS: DG-480-24

Diagrams







STONTRONICS