# CNC precision short drill chuck In accordance with ISO 7388-1 (DIN 69871)



## Application:

For use on machining centres and CNC machines with tool change systems. For drilling, reaming, countersinking and also light milling and finishing tasks.

- $\blacksquare$  100 % concentricity check using different test pin diameters at various measuring points, based on DIN ISO 10888.
- Concentricity tolerance  $\leq$  0.03 mm across the entire clamping range.
- With worm gear.
- Relevant parts hardened and ground.

## Advantage:

- Accident-proof as opening of the chuck during operation or on a sudden spindle stop is not possible.
- Integrated worm gear ensures high retention torque < 75 Nm with 13 mm diameter.

1x CNC precision short drill chuck in accordance with ISO 7388-1 (DIN 69871); incl. hexagon key.

Art. no.	23050 530
Brand	ALBRECHT
Manufacturer Part Number	800 110Z 230 0
Tool holding device	SK 30
Min./max. clamping width	0.5-10 mm
Projecting length	69 mm
Outer diameter	45 mm
Length closed	78 mm
Tapered diameter	38 mm
Clear length	37.5 mm
Concentricity tolerance	0.03 mm
Coolant supply	Internal axial
Balancing quality	G 2.5 at 20 rpm
Gross Weight	0.800 kg
Product Group	209

## **EAN**

4250261589325



