



Section 1. Product and Company Identification.

1.1 Model Number; SCS017 v1
1.2 Description; Chain & Cable Clear Lubricant 500ml Pack of 6

1.3 Manufacturer;

Sealey Group.
 Kempson Way,
 Bury St. Edmunds,
 Suffolk.
 IP32 7AR

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 1 December 2015

Section 2. Hazards Identification.

2.1 Classification of the substance or mixture.

Classification (EC 1272/2008)

| | |
|-------------------------------|---------------------------|
| Physical and Chemical Hazards | Flam. Aerosol 1 - H222 |
| Human health | STOT SE 3 - H336 |
| Environment | Aquatic Chronic 3 - H412. |
| Classification (1999/45/EEC) | F+; R12. R52/53, R67. |

Risk phrases;

R12 Extremely flammable.
 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R65 Harmful: may cause lung damage if swallowed.
 R11 Highly flammable
 R38 Irritating to skin.
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R67 Vapours may cause drowsiness and dizziness.

2.2 Label elements.

Hazard pictogram(s)



Signal Word. Danger

**Hazard statements;**

H222 Extremely flammable aerosol.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.
 H315 Causes skin irritation.
 H220 Extremely flammable gas.
 H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements;

H222 Extremely flammable aerosol.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Supplementary label advice

H280 Contains gas under pressure: May explode if heated.

2.3 Other hazards.

No information available.

Section 3. Substances.

| 3.1 Chemical Name (substance) | 3.1 CAS No. | 3.2 Concentration Volume | Classification | |
|---|-------------|--------------------------|------------------------------|-------------------|
| | | | Hazard Class & Category Code | Hazard Statements |
| BUTANE | 106-97-8 | 10-30% | Flam. Gas 1 Press. Gas | H220 |
| ISOBUTANE | 75-28-5 | 10-30% | Flam. Gas 1 Press. Gas | H220 |
| NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT | 64742-49-0 | 10-30% | Carc. 1B Asp. Tox. 1 | H350 H304 |
| PROPANE | 74-98-6 | 10-30% | Flam. Gas 1 Press. Gas | H220 |

For full text of Phrases and Statements, see Section 16.



Section 4. First Aid Measures.

4.1 Description of first aid measures

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

Skin Contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

Section 5. Fire Fighting Measures.

5.1. Extinguishing media

Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Aerosol cans may explode in a fire.

5.3. Advice for fire-fighters

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.



Section 6. Accidental Release Measures.

6.1. Personal precautions, protective equipment and emergency procedures
No information available.

6.2. Environmental precautions
No information available.

6.3. Methods and material for containment and cleaning up
Wear necessary protective equipment. Extinguish all ignition sources.
Avoid sparks, flames, heat and smoking.
Ventilate.
Let evaporate.
Keep out of confined spaces because of explosion risk.
If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections
See Section 7 for information on Safe Handling
See Section 8 for information of Personal Protective Equipment.
See Section 13 for information on disposal.

Section 7. Handling and Storage.

7.1. Precautions for safe handling
Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact.
Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities
Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)
Intended for use as a Chain & Cable Clear Lubricant, Model Number identified in 1.1 with Description stated in 1.2.



Section 8. Exposure Controls/Personal Protection.

8.1. Control parameters

| Name | STD | TWA - 8 Hrs | | STEL - 15 Min | |
|---|-----|--------------|------------------------|---------------|------------------------|
| | | | | | |
| Butane | WEL | 600 ppm | 1450 mg/m ³ | 750 ppm | 1810 mg/m ³ |
| Naphtha (Petroleum) Hydrotreated Light | | | 1200 mg/m ³ | 60 ppm | 216 mg/m ³ |
| Propane | | Asphyxiating | Asphyxiating | Asphyxiating | Asphyxiating |

WEL = Workplace Exposure Limit.

OES = Occupational Exposure Standard.

MEL = Maximum Exposure Limit

8.2. Exposure controls

Protective equipment



Eye/Face Protection

Use approved safety goggles or face shield.

Skin Protection

Use solvent resisting protective gloves.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Respiratory Protection

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Ventilation

Provide adequate general and local exhaust ventilation.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.



Section 9. Physical and Chemical Properties.

9.1. Information on basic physical and chemical properties

The following information is not a technical specification or sales specification.

| | |
|--|---------------------------|
| (a) Appearance: | Aerosol. |
| (b) Odour: | Characteristic. |
| (c) Odour threshold; | No information available. |
| (d) pH: | No information available. |
| (e) Melting point/freezing point; | No information available. |
| (f) Initial boiling point and boiling range; | No information available. |
| (g) Flash point; | No information available. |
| (h) Evaporation rate; | No information available. |
| (i) Flammability (solid, gas); | No information available. |
| (j) Upper/lower flammability; | Lower; 0.8% Upper; 9.0% |
| (k) Vapour pressure; | No information available. |
| (l) Vapour density; | No information available. |
| (m) Relative density; | No information available. |
| (n) Solubility (ies); | Insoluble in water. |
| (o) Partition coefficient: n-octanol/water; | No information available. |
| (p) Auto-ignition temperature; | No information available. |
| (q) Decomposition temperature; | No information available. |
| (r) Viscosity; | No information available. |
| (s) Explosive properties; | No information available. |
| (t) Oxidising properties. | No information available. |

Section 10. Stability and Reactivity.

| | |
|---|--|
| 10.1. Reactivity | No information available. |
| 10.2. Chemical stability | Stable under normal temperature conditions. |
| 10.3. Possibility of hazardous reactions | No information available. |
| 10.4. Conditions to avoid | Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids. |
| 10.5. Incompatible materials | No information available. |
| 10.6. Hazardous decomposition products | Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂). |



Section 11. Toxicological Information.

11.1. Information on toxicological effects

Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact

Irritating to eyes. May cause chemical eye burns.

Route of entry

Inhalation. Skin and/or eye contact.

Section 12. Ecological Information.

Dangerous for the environment if discharged into watercourses.

| | |
|--|---------------------------|
| 12.1. Toxicity | No information available. |
| 12.2. Persistence and degradability | No information available. |
| 12.3. Bioaccumulative potential | No information available. |
| 12.4. Mobility in soil | No information available. |
| 12.5. Results of PBT and vPvB assessment | No information available. |
| 12.6. Other adverse effects | No information available. |

Section 13. Disposal Considerations.

13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.



Section 14. Transport Information.

ADR. International Carriage of Dangerous Goods by Road.

| | | |
|---|---|-------------|
| 14.1. UN number | UN 1950 | |
| 14.2. Name and Description | AEROSOLS, flammable | |
| | Label | 2.1 |
| | Special Provisions | 190 344 625 |
| | Limited Quantities | 1 L |
| | Excepted Quantities | E0 |
| | Packing Instructions | P207, LP02 |
| | Special Packaging Provisions | RR6 L2 |
| 14.3. Transport hazard class(es) | Class | 2 |
| | Classification Code | 5F |
| | Transport Category | 2 |
| | Tunnel restriction code | D |
| 14.4. Packing group | - | |
| 14.5. Environmental hazards | Avoid release to the environment | |
| 14.6. Special precautions for user | Refer to Section 2.2 Precautionary Statements | |

IATA. International Air Transport Association.

| | | |
|--|----------------------|---------------|
| 14.1. UN number | UN 1950 | |
| 14.2. UN Proper Shipping Name/Description | AEROSOLS, flammable | |
| | Hazard Label. | Flamm. gas |
| | Excepted Quantity | E0 |
| | Packing Instructions | Passenger 203 |
| | | Ltd Qty Y203 |
| | | Cargo 203 |
| | | ERG Code 10L |
| | Special Provisions | A167 |

Special Provision A802.

Notwithstanding the absence of a packing group in column E, substances and article assigned to these entries must be packed in UN Specification packagings that meet packing group II performance standards. This does not apply when aerosols are prepared for transport in accordance with the limited quantity provisions.

| | | |
|---|---|-----|
| 14.3. Transport hazard class(es) | Class or Division | 2.1 |
| 14.4. Packing group | - | |
| 14.5. Environmental hazards | Avoid release to the environment | |
| 14.6. Special precautions for user | Refer to Section 2.2 Precautionary Statements | |

IMDG. International Maritime Dangerous Goods.

| | |
|---|--|
| 14.1. UN number | UN 1950 |
| 14.2. UN proper shipping name | AEROSOLS, flammable |
| | Special Provisions 63, 190 277, 327, 344, 959 |
| | Limited Quantities See Special Provision 277 |
| | Excepted Quantities E0 |
| | Packing Instructions P207, LP02 |
| | Packaging Provisions PP87, L2 |
| 14.3. Transport hazard class(es) | Class or Division 2 |
| | Subsidiary Risk(s) See Special Provision 63 |
| 14.4. Packing group | - |
| 14.5. Environmental hazards | Avoid release to the environment |
| 14.6. Special precautions for user | Refer to Section 2.2 Precautionary Statements |
| 14.7. Transport in bulk – Maritime only. | Bulk transport is not applicable to this product |



Section 15. Regulatory Information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
No information available.

15.2. Chemical safety assessment
No information available.

Section 16. Additional Information.

Full text of Phrases and Statements used in Section 3;

H220: Extremely flammable gas.

H304: May be fatal if swallowed and enters airways.

H350: May cause cancer.

The above information is believed to be accurate and represents the best information currently available.

No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.

| Issue level | Date | Revisions |
|-------------|----------|--------------------------|
| 1 | 12/02/16 | First issue. |
| 2 | 14/09/16 | Sections 3, 14, 15 & 16. |
| | | |
| | | |

End of Safety Data Sheet.