

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of XRCGB25M000F3A1AR0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=XRCGB25M000F3A1AR0

XRCGB25M000F3A1AR0












Appearance & Shape







Features

The crystal unit for automotive electronics that realized small package and highly accurate frequency.

Based on Murata's excellent package technology and high grade quartz crystal elements, achieving small size and high accuracy

Features

- 1. The series has high reliability and is available for a wide temperature range.
- 2. The crystal unit is small size (2.0 x 1.6 x 0.7 (mm)), and contribute to reduction in mounting area.
- 3. The series complies to RoHS and ELV directives, being leadfree (phase 3).
- 4. The series complies to AEC-Q200.



Applications

| Automotive Usage | Powertrain/Safety |
|------------------|-------------------|
| Other Usage | Automotive |



Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|--------------------|---------------------------------|
| R0 | 180mm Plastic Tape | 3000 |

1 of 2

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of XRCGB25M000F3A1AR0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=XRCGB25M000F3A1AR0

XRCGB25M000F3A1AR0



Specifications

| Product Type | Crystal Unit |
|---------------------------------------|--------------------------|
| Series | XRCGB |
| Туре | HCR2016 |
| Frequency | 25.0000MHz |
| Frequency Tolerance | +/-30ppm max. (25+/-3°C) |
| Operating Temperature Range | -40°C~125°C |
| Frequency Shift by Temperature | +/-35ppm max. |
| Frequency Aging | +/-2ppm max./year |
| Equivalent Series Resistance (ESR) | 100ohm max. |
| Drive Level (DL) | 150μW (300μW max.) |
| Load Capacitance (Cs) | 6pF |
| Shape | SMD |
| Wash | Not available |
| L x W (size) | 2.0x1.6mm |
| Mass | 6.9mg |

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

