


U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>ÖLFLEX® CLASSIC 110 H</b>	05.11.2015

Halogen-free control cable, oil resistant and very flexible  
 Easy handling and installation due to very flexible cable type  
 Wide application range due to excellent product features  
 Certified for maritime applications



Good chemical resistance



Flame-retardant



Single halogen-free cable



Cold-resistant



Oil-resistant



UV-resistant

#### Info

New: Extended application range due to GL certification  
 High flexibility and oil-resistance  
 VDE-certified

#### Application range

Public buildings like airports or railway stations  
 Plant engineering, Industrial machinery  
 Heating and air-conditioning systems  
 Stage applications


Particularly where human and animal life as well as valuable property are exposed to high risk of fire hazards  
 Intended for use under the European Construction Product Regulation (CPR), refer to catalogue appendix T14

Note: for the use of AWM (Appliance Wiring Material) cables in industrial machinery (USA) according to NFPA 79 Ed. 2015: please see the catalogue appendix table T29

#### Product Make-up

Fine-wire strand made of bare copper wires  
 Core insulation: Halogen-free  
 Cores twisted in layers  
 Outer sheath made of special halogen-free compound, grey (RAL 7001)

Product Management	Document: LAPP_PRO25EN.pdf	1 / 4
--------------------	----------------------------	-------

U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
<b>ÖLFLEX® CLASSIC 110 H</b>		05.11.2015

### Norm references / Approvals

UL AWM style 21089  
Based on EN 50525-3-11  
Based on EN 50525-2-51  
Germanischer Lloyd (GL)  
certificate no. 11 119-14 HH

### Product features

Flame-retardant according to IEC 60332-1-2  
(flame spread on a single cable)  
No flame-propagation according to IEC 60332-3-22 and IEC 60332-3-24 respectively IEC 60332-3-25 (Flame spread on vertical cable or wire bundle)  
Halogen-free according to IEC 60754-1  
(amount of halogen acid gas)  
Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity)  
Low smoke density according to IEC 61034-2  
Oil-resistant according to EN 50363-4-1 (TM5)  
and UL OIL RES I and UL OIL RES II  
UV and weather-resistant according to ISO 4892-2  
Ozone-resistant according to EN 50396

### Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum  
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).  
Photographs are not to scale and do not represent detailed images of the respective products.

### Technical Data

Core identification code:	Black with white numbers acc. to VDE 0293-1
Classification:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Conductor stranding:	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Minimum bending radius:	Occasional flexing: 10 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage:	U <sub>0</sub> /U: 300/500 V UL: 600 V
Test voltage:	4000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	Occasional flexing: -30°C to +70°C (UL: +75°C) Fixed installation: -40°C to +80°C (UL: +75°C)

Product Management	Document: LAPP_PRO25EN.pdf	2 / 4
--------------------	----------------------------	-------

## ÖLFLEX® CLASSIC 110 H

05.11.2015

Part number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 110 H U <sub>0</sub> /U: 300/500 V				
10019900	2 X 0,5	5,1	9.6	41
10019901	3 G 0,5	5,4	14.4	49
10019902	3 X 0,5	5,4	14.4	49
10019903	4 G 0,5	5,8	19.2	58
10019904	4 X 0,5	5,8	19.2	58
10019905	5 G 0,5	6,3	24.0	69
10019906	7 G 0,5	6,9	33.6	87
10019907	12 G 0,5	9,1	57.6	141
10019910	2 X 0,75	5,5	14.4	51
10019911	3 G 0,75	5,8	21.6	61
10019912	3 X 0,75	5,8	21.6	61
10019913	4 G 0,75	6,3	28.8	73
10019914	4 X 0,75	6,3	28.8	73
10019915	5 G 0,75	6,9	36.0	87
10019916	5 X 0,75	6,9	36.0	87
10019917	7 G 0,75	7,5	50.4	111
10019918	7 X 0,75	7,5	50.4	111
10019919	9 G 0,75	9,6	64.8	150
10019920	12 G 0,75	10,1	86.4	186
10019921	18 G 0,75	12,0	129.6	265
10019922	25 G 0,75	14,1	180.0	365
10019960	2 X 1,0	5,8	19.2	59
10019961	3 G 1,0	6,1	28.8	72
10019962	3 X 1,0	6,1	28.8	72
10019963	4 G 1,0	6,6	38.4	87
10019964	4 X 1,0	6,6	38.4	87
10019965	5 G 1,0	7,3	48.0	104
10019967	7 G 1,0	8,1	67.2	138
10019968	8 G 1,0	9,7	76.8	164
10019969	12 G 1,0	10,7	115.2	225
10019970	14 G 1,0	11,4	134.4	261
10019971	18 G 1,0	12,9	172.8	328
10019972	25 G 1,0	15,0	240.0	445

Part number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
10019973	41 G 1,0	19,2	393.6	719
10019930	2 X 1,5	6,4	28.8	76
10019931	3 G 1,5	6,8	43.2	94
10019980	3 X 1,5	6,8	43.2	94
10019932	4 G 1,5	7,4	57.6	115
10019933	5 G 1,5	8,3	72.0	142
10019934	7 G 1,5	9.0	100.8	184
10019981	8 G 1,5	10,8	115.2	218
10019982	9 G 1,5	11,6	129.6	245
10019935	12 G 1,5	12,2	172.8	308
10019936	14 G 1,5	13.0	201.6	357
10019937	18 G 1,5	14,6	259.2	449
10019938	25 G 1,5	17,2	360.0	617
10019927	34 G 1,5	19,8	489.6	821
10019944	2 X 2,5	7,6	48.0	113
10019945	3 G 2,5	8,3	72.0	146
10019946	4 G 2,5	9.0	96.0	180
10019947	5 G 2,5	10,1	120.0	221
10019948	7 G 2,5	11,2	168.0	295
10019949	12 G 2,5	15,1	288.0	491
10019950	4 G 4	10,8	153.6	268
10019951	5 G 4	12,1	192.0	328
10019952	7 G 4	13,4	268.8	438
10019953	4 G 6	13.0	230.4	391
10019954	5 G 6	14,5	288.0	478
10019975	7 G 6	16.0	403.2	638
10019851	4 G 10	16,2	384.0	635
10019852	5 G 10	18,1	480.0	775
10019849	4 G 16	18,8	614.4	930
10019853	5 G 16	21,2	768.0	1147
10019854	4 G 25	23,5	960.0	1442
10019855	5 G 25	26,4	1200.0	1773
10019856	4 G 35	26,6	1344.0	1917