



Material Safety Data Sheet

1. Product & Company Identification

Product:	Primary silver oxide battery button cell (size 390/SR54)
Manufacturer:	Conrad Electronic SE
Nominal voltage:	1,55 V
Nominal capacity:	80 mAh
Address:	Klaus-Conrad-Str. 1, D-92240 Hirschau
Telephone:	+49 (0) 9604 / 40 - 8988
Date of issue:	31.03.2014

Electrochemical system: Zinc/mercury | NaOH/KOH electrolyte | silver oxide, manganese dioxide

Anode (negative electrode): Zinc/mercury

Cathode (positive electrode): Silver oxide, manganese dioxide

Legal Remark (U.S.A.)

Material Safety Data Sheets (MSDS) are a sub-requirement of the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR Subpart 1910.1200. This Hazard Communication Standard does not apply to various subcategories including anything defined by OSHA as an "article". OSHA has defined "article" as a manufactured item other than a fluid or particle; (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g. minute or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees.

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard.

Legal remark (EU)

These batteries are no "substances" or "preparations" according to Regulation (EC) No 1907/2006 EC. Instead they have to be regarded as "articles", no substances are intended to be released during handling. Therefore there is no obligation to supply a MSDS according to Regulation (EC) 1907/2006, Article 31.

General remark

This "Safety Information" is provided as a service to our customers. The details presented are in accordance with our present knowledge and experiences. They are no contractual assurances of product attributes.



Material Safety Data Sheet

2. Hazards Identification

A sealed zinc/silver oxide button cell is not hazardous in normal use (as defined in chapter 7).

In case of mistreatment (prolonged deep discharge, charge, reverse charge, external short circuit...) and in case of fault, some electrolyte can leak from the cell. In these cases refer to the risk of potassium hydroxide solution or sodium hydroxide solution (corrosive, pH > 14). Charging may cause rupture. The electrode materials are only hazardous, if the materials are released by mechanical damaging of the cell or if exposed to fire.

3. Composition/information on ingredients

Ingredients

Contents	CAS No.	Hazard Symbols	R Phrases	Material
5 - 35 %	20667-12-3	O, C, Xi	R8-34-44	Silver Oxide
0 - 20%	1313-13-9	Xn	R20/22	Manganese dioxide
5 - 10%	7440-66-6	N	R 50/53	Zinc
0 - 3 %	1310-58-3	C	R 22-35	Potassium hydroxide
0 - 2%	1310-73-2	C	R35	Sodium hydroxide
0,15 - 0,5 % < 25 mg/cell	7439-97-6	T, N	R 23-33-50/53	Mercury (in zinc alloy)

Heavy Metals

Contents	CAS No.	Material
20 - 60 mg/kg	7439-92-1	Lead
< 5 mg/kg	7440-43-9	Cadmium

Other Ingredients

Contents	CAS No.	Material
27 - 70 %		Nickel plated steel
2 - 5 %		Copper
2 - 7 %		Polymers

4. First aid measures

Measures at accidental release

After inhalation: Fresh air. Seek for medical assistance.

After skin contact: Flush affected areas with plenty of water. Remove contaminated cloth immediately. Seek for medical assistance.

After eye contact: Flush the eye gently with plenty of water (at least 15 minutes). Seek for medical assistance.

After ingestion: Drink plenty of water. Avoid vomiting. Seek for medical assistance. No trials for neutralization.



Material Safety Data Sheet

5. Fire fighting measures

Suitable extinguishing media:

Use foam, water, or CO₂, as appropriate.

Extinguishing media with limited suitability:

(none)

Special protection equipment during fire-fighting:

Contamination cloth including breathing apparatus.

Special hazard:

(none)

6. Accidental release measures

Person related measures:

Wear personal protective equipment adapted to the situation (protection gloves, cloth).

Environment protection measures:

In the event of battery rupture, prevent skin contact and collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

Treatment for cleaning:

If battery casing is dismantled, small amounts of electrolyte may leak. Pack the battery including ingredients as described above. Then clean with water (diluted acetic acid may be helpful).

7. Handling and storage

Guideline for safe handling:

Always follow the warning information on the batteries and in the manuals of devices. Only use the recommended battery types. Keep batteries away from children. For devices to be used by children, the battery casing should be protected against unauthorized access. Unpacked batteries shall not lie about in bulk. In case of battery change always replace all batteries by new ones of identical type and brand. Do not swallow batteries. Do not throw batteries into water. Do not throw batteries into fire. Do not short-circuit batteries. Do not recharge primary batteries. Do not open or disassemble batteries.

Storage:

Storage preferably at room temperature (approx. 20°C). Avoid large temperature changes. Avoid direct sunlight. At higher temperature the electrical performance may be reduced. Storage of unpacked batteries can cause short circuit and heat generation.

Storage of large amounts:

If possible, store the batteries in original packaging (short circuit protection); A fire alarm is recommended; For automatic fire extinction consider chapter 5 "Fire fighting measures".

VCI storage category:

It is recommended to consider the "VCI Guideline for the mixed storage of chemicals" and to handle primary button cells according to storage category 11 ("combustible solids").



Material Safety Data Sheet

8. Exposure controls/personal protection

Under normal conditions (discharge, avoid prolonged deep discharge) release of ingredients does not occur.

9. Physical and chemical properties

Not applicable if closed.

10. Stability and reactivity

Dangerous reactions:

When heated above 70°C the risk of rupture occurs.

11. Toxicological information

Under normal conditions (during discharge) release of ingredients does not occur. If accidental release occurs see information in section 2, 3, and 4. Swallowing of a battery can be harmful. Call the local Poison Control Centre for advice and follow-up.

12. Ecological information

Our primary zinc/silver button cells do contain mercury and lead, and do not contain cadmium as defined by the European directive 2006/66/EC Article 21; they comply with the chemical composition requirements of this Directive. The mercury content is in accordance with the "Mercury-Containing and Rechargeable Battery Management Act" (U.S.A.).

13. Disposal considerations

USA: Primary zinc/silver button cells are classified by the federal government as non-hazardous waste and are safe for disposal in the normal municipal waste stream.

In the European Union, manufacturing, handling and disposal of batteries is regulated on the basis of the DIRECTIVE 2006/66/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 6 September 2006 on batteries and accumulators and waste batteries and accumulators and repealing Directive 91/157/EEC. Customers find detailed information on disposal in their specific countries using the web site of the European Portable Batteries Association (http://www.epbaeurope.net/legislation_national.html).

Importers and users outside EU should consider the local law and rules.

In order to avoid short circuit and heating, used zinc/silver button cells should never be stored or transported in bulk. Proper measures against short circuit are:

- Storage of batteries in original packaging
- Coverage of the terminals



Material Safety Data Sheet

14. Transport information

General considerations

Our primary zinc/silver oxide button cells are considered to be "dry cell" batteries and are unregulated for purposes of transportation by the U.S. Department of Transportation (DOT), International Civil Aviation Administration (ICAO), International Air Transport Association (IATA), the International Maritime Organization (IMO), the "Accord Européen Relatif au Transport International des Marchandises Dangereuses par Route" (ADR) and the "Règlement concernant le transport international ferroviaire de marchandises Dangereuses" (RID).

IATA DGR

Special Provision A123: "Examples of such batteries are: alkali-manganese, zinc-carbon, nickel-metal hydride and nickel-cadmium batteries. Any electrical battery ... having the potential of a dangerous evolution of heat must be prepared for transport as to prevent (a) a short-circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals...) is forbidden from transport; and (b) accidental activation. The words "Not Restricted" and the Special Provision number must be included in the description of the substance on the Air Waybill as required by 8.2.6, when an Air Waybill is issued."

EU

Special Provision 304 (ADR/RID): „Batteries, dry, containing corrosive electrolyte which will not flow out of the battery if the battery case is cracked are not subject to the requirements of RID/ADR provided the batteries are securely packed and protected against short-circuits. Examples of such batteries are: alkali-manganese, zinc-carbon, nickel-metal hydride and nickel-cadmium batteries.

USA

49 CFR § 172.102 Special Provision 130: „... „Batteries, dry, sealed, n.o.s.“ are not subject to any other requirements of this subchapter except for the following: ...Batteries and battery-powered device(s) containing batteries must be prepared and packaged for transport in a manner to prevent: (i) A dangerous evolution of heat; (ii) Short circuits... (iii) Damage to terminals ...“

15. Regulatory information

Marking consideration:

According to DIRECTIVE 2006/66/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 6 September 2006 on batteries and accumulators and waste batteries and accumulators and repealing Directive 91/157/EEC all batteries have to be marked with the crossed bin; according to Article 21 of this directive primary zinc/silver oxide button cells have to be marked with the element symbols "Hg" and "Pb". Due to the size of the battery, this marking has to be placed on the packaging.

International safety standards:

IEC 60086-5.

Water hazard class:

(according to German Federal Water Management Act) non-water pollution according to VwVwS Appendix 1 (No. 1443 and 766)



Material Safety Data Sheet

16. Other information

Full text of Classification and R Phrases referred to under sections 2 and 3

Classification	Xn	Harmful
	T	Toxic
	Xi	Irritating
	O	Oxidising
	C	Corrosive
	N	Dangerous for the environment
R Phrases	8	Contact with combustible material may cause fire
	20/22	Harmful by inhalation and if swallowed.
	22	Harmful if swallowed.
	33	Danger of cumulative effects
	34	Causes burns.
	35	Causes severe burns.
	44	Risk of explosion if heated under confinement.
50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	

Note:

Date of issue of the transport regulations: ADR 2009, IATA 2010, IMDG 2006, DOT / 49 CFR 2010.