



Non-contact Voltage Tester with Shielded Fork Tip, 230v AC

➤ Volt Stick Pro230 Non-contact Voltage Tester with unique shielded fork tip, 230v AC

Unique to the market, the **Volt Stick Pro230**.

Features a specially-designed 'shielded' fork tip for highly selective and accurate testing for presence of AC voltage in specific cables, wires or conductors,

This professional instant voltage tester is designed to safely check for the presence of an AC voltage, without making any disconnections in cables, wall sockets, fuses, circuit breakers, junction boxes, etc.

The Volt Stick PRO230 is ideal for professional, close proximity testing and installation work.

The Volt Stick PRO230 is also supplied with an adaptor for 'standard' cable testing (ie. where selective cable conductor testing is not required and testing larger cables).

Features:

- Unique forked tip gives unsurpassed selectivity and reduces the risk of spurious indications
- Live cables can easily be detected in equipment cabinets, fuse boxes, etc
- Cables and connections can easily be checked in low voltage equipment too
- Extremely safe when measuring in junction boxes
- With the supplied field strength amplifier, anti-tamper, earthed outlets can be checked
- Powerful red light in the tip to indicate voltage
- Fully insulated for safe use
- Includes Adaptor for larger cable testing
- Approved to IEC 61010-1, CATIII 1000VAC and CE

Applications:

- Visual and audible indicators ideal for high sunlight areas and 'indication 'round corners'
- 230v AC Mains testing
- Finds breaks in cables
- Polarity checking



Selective Polarity Identification



Highly Populated Control Panel Wiring



Selective Core Cable Identification

Attribute	Value
Voltage range	230v ~ 1000v AC
Sensitivity	Functions upon contact with cable carrying 220v AC
Response Time	Immediate
Intrinsically Safe	No
Power Requirements	2 x AAA (LR03) batteries (supplied)
Relative Humidity	80% @ 30°C, 50% @ 40°C
Operating Temperatures	-10° ~ +50°C
Overvoltage	CATIII, 1000v AC
Dimensions	145(L) x 18(Ø)mm
Weight (Net)	0.04kg

