## **Power Cords**

# multicomp PRO




### **Specifications**

Connector to Connector : SI 32 Plug to IEC 60320 C7

**Current Rating** : 2.5A : 250V Voltage Rating Jacket Colour : Black

### RoHS **Compliant**


### Diagram



INDENT MARKING:

INDENT MARKNING: LFC-2F∢VDE> KEMA-KEUR∢SEMKO Þ∢ DEMKO Þ∢ NEMKO Þ∢ FIMKO Þ∢ CEBEC 618 ÞØŸE Þ +∨ +∨ +∨ +∨ IEMMEQU NF-USE-1291-H03VVH2-F 2X0.75mm ³XXXX

YEAR 



No.	Description	Qty
1	H03VVH2-F 0.75mm² 2C Black	
2	(Molded Plug) LP-55 2.5A/250V	
3	(Molded Connector) LS-7P 2.5A 250V	1
4	Mini Tie	
5	Label	]

### **Notes**

1. Cable : The Cord Shall Comply with IEC60227. 2. Plug : The Molded Plug Shall Comply with SI 32.

All of Power Plug Shall be Nickel Plated, and no Corrosion Allowed

After 24H Salt Spray Test by Following ISO 9227.

3. Connector: The Molded Connector Shall Comply with IEC60320-1 Standard (C7 Connector).

4. Colour : Black

#### **Part Number Table**

Description	Length Part Number	
Power Cords, IEC 60320-1 C7 to SI 32 Plug, Black	1000mm	GW-151781
Power Cords, IEC 60320-1 C7 to SI 32 Plug, Black	2000mm	GW-151782

**Dimensions: Millimetres** 

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

