

DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 30.01.2017
1.5	24.04.2017	3267974-00006	Date of first issue: 15.12.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	: DOW CORNING(R) 786 SILICONE SEALANT M CLEAR	
Product code	: 0000000004023914	
1.2 Relevant identified uses of th	e substance or mixture and uses advised against	
Use of the Sub- stance/Mixture	: Adhesive, binding agents	
1.3 Details of the supplier of the	safety data sheet	
Company	Dow Corning Europe S.A. rue Jules Bordet - Parc Industriel - Zone C B-7180 Seneffe	
Telephone	: English Tel: +49 611237507	

		Deutsch Tel: Français Tel: Italiano Tel: Español Tel:	+49 611237500 +32 64511149 +32 64511170 +32 64511163
E-mail address of person responsible for the SDS	:	sdseu@dowco	orning.com

1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350 Dow Corning (Wiesbaden 24h) Tél: +49 61122158 Dow Corning (Seneffe 24h) Tel: +32 64 888240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

2

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Precautionary statements

Prevention:

P271 Use only outdoors or in a well-ventilated area.



DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 30.01.2017
1.5	24.04.2017	3267974-00006	Date of first issue: 15.12.2015

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature	:	Silicone elastomer
Hazardous components		
Remarks	:	No hazardous ingredients

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders	:	No special precautions are necessary for first aid responders.
If inhaled	:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	:	Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact	:	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment
- : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	None known.

DOW CORNING

DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Version 1.5	Revision Date: 24.04.2017		DS Number: 67974-00006	Date of last issue: 30.01.2017 Date of first issue: 15.12.2015	
5.2 Special hazards arising from Specific hazards during fire- fighting				xture bustion products may be a hazard to health.	
Ha uct	zardous combustion prod- s	: Carbon oxides Silicon oxides Formaldehyde			
5.3 Adv	5.3 Advice for firefighters				
	ecial protective equipment firefighters	:		ed breathing apparatus for firefighting if nec- onal protective equipment.	
Sp od	ecific extinguishing meth- s	:	cumstances and t Use water spray t	measures that are appropriate to local cir- he surrounding environment. o cool unopened containers. ged containers from fire area if it is safe to do	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

o. i reisonai piecautions, piotec	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	e equipment and emergency procedures
Personal precautions	:	Follow safe handling advice and personal protective equip- ment recommendations.
6.2 Environmental precautions		
Environmental precautions	:	Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	 Soak up with inert absorbent material. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.



DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 30.01.2017
1.5	24.04.2017	3267974-00006	Date of first issue: 15.12.2015

SECTION 7: Handling and storage

7.1 Precautions for safe handling				
Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.		
Local/Total ventilation	:	Use only with adequate ventilation.		
Advice on safe handling	:	Handle in accordance with good industrial hygiene and safety practice. Take care to prevent spills, waste and minimize release to the environment.		
Hygiene measures	:	Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.		
7.2 Conditions for safe storage,	incl	uding any incompatibilities		
Requirements for storage areas and containers	:	Keep in properly labelled containers. Store in accordance with the particular national regulations.		
Advice on common storage	:	Do not store with the following product types: Strong oxidizing agents		
7.3 Specific end use(s)				
Specific use(s)	:	These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.		

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Silicon dioxide	7631-86-9	TWA (inhalable dust)	6 mg/m3 (Silica)	GB EH40
Further information	fractions of air in accordance sampling and COSHH defin kind when pre 8-hour TWA of This means the above these left	borne dust which wi with the methods de gravimetric analysis ition of a substance sent at a concentrat of inhalable dust or 4 hat any dust will be s evels. Some dusts h	espirable dust and inhalable Il be collected when sampling escribed in MDHS14/3 Gene of respirable and inhalable of hazardous to health includes ion in air equal to or greater mg.m-3 8-hour TWA of resp ubject to COSHH if people a ave been assigned specific V the appropriate limit., Most ir	g is undertaken ral methods for lust, The dust of any than 10 mg.m-3 irable dust. re exposed VELs and ex-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Version 1.5	Revision Da 24.04.2017			ate of last issue: 30.01.2017 ate of first issue: 15.12.2015	
Furthe	er information	of any particular body response the HSE distinguishes ble' and 'respirate material that entre available for dep to the fraction the definitions and e contain components should be completed a figure three time To the purposes fractions of airboo in accordance w sampling and gra COSHH definition kind when prese 8-hour TWA of in This means that above these level posure to these contain particular body response the HSE distinguishes ble' and 'respirate material that entre available for dep to the fraction the definitions and e contain components should be completed	particle after ent hat it elicits, depe es two size fracti- obe'., Inhalable du ers the nose and osition in the res- at penetrates to a xplanatory mater ents that have the ied with., Where <u>nes the long-term</u> WA (Respirable <u>ust)</u> s of these limits, orne dust which w ith the methods of avimetric analysis on of a substance nt at a concentra nhalable dust or any dust will be els. Some dusts I must comply with of a wide range particle after ent hat it elicits, depe es two size fracti- ble'., Inhalable du ers the nose and osition in the res at penetrates to a xplanatory mater ents that have the ied with., Where	of sizes. The behaviour, dep ry into the human respiratory and on the nature and size of ons for limit-setting purposes ust approximates to the fracti mouth during breathing and piratory tract. Respirable dus the gas exchange region of the rial are given in MDHS14/3., eir own assigned WEL, all the no specific short-term expose exposure should be used 2.4 mg/m3 (Silica) respirable dust and inhalable vill be collected when samplin described in MDHS14/3 Gen s of respirable and inhalable thazardous to health include the appropriate limit., Most of sizes. The behaviour, dep ry into the human respiratory and on the nature and size of ons for limit-setting purposes ust approximates to the fracti mouth during breathing and piratory tract. Respirable dus the gas exchange region of the rial are given in MDHS14/3., eir own assigned WEL, all the no specific short-term exposes and piratory tract. Respirable dus the gas exchange region of the fraction of the approximates to the fraction point during breathing and piratory tract. Respirable dus the gas exchange region of the rial are given in MDHS14/3., eir own assigned WEL, all the no specific short-term exposes and exposure should be used	y system and the the particle. termed 'inhala- on of airborne is therefore st approximates he lung. Fuller Where dusts e relevant limits sure limit is listed, GB EH40 dust are those ng is undertaken eral methods for dust, The s dust of any than 10 mg.m-3 pirable dust. are exposed WELs and ex- industrial dusts osition and fate y system and the the particle. termed 'inhala- on of airborne is therefore st approximates he lung. Fuller Where dusts e relevant limits

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Silicon dioxide

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10). Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

:

Personal protective equipment

Eye protection

Wear the following personal protective equipment: Safety glasses

DOW CORNING

DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Version 1.5	Revision Date: 24.04.2017	SDS Number: 3267974-00006	Date of last issue: 30.01.2017 Date of first issue: 15.12.2015			
Hand protection Remarks		: Wash hands b	: Wash hands before breaks and at the end of workday.			
Skin and body protection		: Skin should be	Skin should be washed after contact.			
Respiratory protection		: No personal re quired.	espiratory protective equipment normally re-			

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	paste
Colour	:	colourless
Odour	:	Acetic acid
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	No data available
Relative density	:	1.04
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	No data available



DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Versio 1.5	on Revision Date: 24.04.2017	SDS Number:Date of last issue: 30.01.20173267974-00006Date of first issue: 15.12.2015			
E	Decomposition temperature	: No data available			
١	/iscosity Viscosity, dynamic	: Not applicable			
E	Explosive properties	: Not explosive			
C	Dxidizing properties	: The substance or mixture is not classified as oxidizing.			
	ther information Molecular weight	: No data available			
F	Particle size	: No data available			
S	Self-ignition	: The substance or mixture is not classified as pyrophoric. substance or mixture is not classified as self heating.	The		

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	 Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Acetic acid is formed upon contact with water or humid air. Hazardous decomposition products will be formed at elevated temperatures.
10.4 Conditions to avoid	

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

Thermal decomposition : Formaldehyde

SECTION 11: Toxicological information

11.1 Information on toxicological effects



DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Versio 1.5	on	Revision Date: 24.04.2017		DS Number: 67974-00006		st issue: 30.01.2017 st issue: 15.12.2015		
In e:								
	Acute toxicity Not classified based on available information.							
_		orrosion/irritation ssified based on availa	ble	information.				
R		: t: No skin irritation <s: based="" data="" from<="" on="" td=""><td>ı sir</td><td>nilar materials</td><td></td><td></td></s:>	ı sir	nilar materials				
		s eye damage/eye irri ssified based on availa						
R	Product: Result: No eye irritation Remarks: Based on data from similar materials							
R	Respira	atory or skin sensitis	atic	on				
_		ensitisation ssified based on availa	ble	information.				
	-	atory sensitisation ssified based on availa	ble	information.				
		cell mutagenicity ssified based on availa	ble	information.				
	Carcinogenicity Not classified based on available information.							
	Reproductive toxicity Not classified based on available information.							
	STOT - single exposure Not classified based on available information.							
	STOT - repeated exposure Not classified based on available information.							
	Aspiration toxicity Not classified based on available information.							
SECT		12: Ecological infor	ma	ntion				
12.1 T	oxicit	у						

No data available



DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 30.01.2017
1.5	24.04.2017	3267974-00006	Date of first issue: 15.12.2015

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.



DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 30.01.2017
1.5	24.04.2017	3267974-00006	Date of first issue: 15.12.2015

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Dimethylbis[(1- oxoneodecyl)oxy]stannane (20)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer	:	Not applicable
Regulation (EC) No 850/2004 on persistent organic pol- lutants	:	Not applicable
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

The components of this product are reported in the following inventories: NZIoC : All ingredients listed or exempt.					
AICS	:	All ingredients listed or exempt.			
IECSC	:	All ingredients listed or exempt.			
PICCS	:	All ingredients listed or exempt.			
DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).			
REACH	:	For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.			
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.			
TCSI	:	All ingredients listed or exempt.			

DOW CORNING

DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Version	Revisi
1.5	24.04.

ion Date: .2017 SDS Number: 3267974-00006

Date of last issue: 30.01.2017 Date of first issue: 15.12.2015

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of other abbreviations

GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to : Inter compile the Safety Data eChe Sheet cy, h

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.



DOW CORNING(R) 786 SILICONE SEALANT M CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 30.01.2017
1.5	24.04.2017	3267974-00006	Date of first issue: 15.12.2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN