

Accel 10 Click



PID: MIKROE-4112

Accel 10 Click features an ultra-low power triaxial "femto" accelerometer sensor with embedded intelligence, labeled as the LIS2DW12TR. This Click board™ allows linear motion and gravitational force measurements in ranges of ± 2 g, ± 4 g, ± 8 , and ± 16 g in three perpendicular axes. This smart sensor allows the Accel 10 Click to detect many different events, including tap, double tap, free-fall detection, and more, making it well suited for using it in handheld or wearable devices. It features an onboard data processing, offering the acceleration data directly, over the standard I2C or SPI interface.

Accel 10 Click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board™ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS™ socket.

The sensor can use any of its two interrupt pins to report a detected event.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
 ISO 14001: 2015 certification of environmental management system.
 OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

Specifications

Type	Motion,Acceleration
Applications	Accel 10 click can be used for a rapid development and testing of various applications based on step counting, fitness applications, profile switching and display ON/OFF applications, angle measurement applications, and similar applications.
On-board modules	LIS2DW12TR, a 14-bit triaxial acceleration sensor with ultra-low power consumption, from STMicroelectronics.
Key Features	tap, double tap and free-fall detection, ultra-low power consumption, thermal readings
Interface	GPIO,SPI,I2C
Compatibility	mikroBUS
Click board size	S (28.6 x 25.4 mm)
Input Voltage	3.3V

Resources

[mikroBUS™ Standard specification](#)

[LibStock: mikroSDK](#)

[Click board catalog](#)

[Click boards™ Standard Page](#)

Downloads

[Accel 10 click 2D and 3D files](#)

[Accel 10 click example on Libstock](#)

[LIS2DW12TR datasheet](#)

[Accel 10 click schematic](#)

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system.
 ISO 14001: 2015 certification of environmental management system.
 OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).