

Product/Process Change Notice - PCN 12_0306 Rev. -

Analog Devices, Inc. Three Technology Way Norwood, Massachusetts 02062-9106

This notice is to inform you of a change that will be made to certain ADI products (see Material Report). Any issues with this PCN or requirements to qualify the change (additional data or samples) must be sent to ADI within 30 days of publication date. ADI contact information is listed below.

PCN Title: ADuCM360/ADuCM361 Kernal Revision

Publication Date: 28-Nov-2012

Effectivity Date: 28-Nov-2012 (the earliest date that a customer could expect to receive changed material)

vision Description:
ial Release
scription Of Change
rnal revision from D30 to D31 teleprocess to the kernel revision. Existing released silicon is revision 0. The updated kernel that will have the fix in place for better sh read protection will be revision 1.
ason For Change
prove flash read protection security
revision 1 of the kernel, an extra step is required to ensure the user flash space is always protected. for 128kB parts, the user must set flash address 0x1FFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 e kernel will read this flash location and only enable the Serial Wire interface if the flash location does not contain this value. the current D30 parts, the kernel always enables the serial wire interface on exiting the kernel. Therefore, there is a short time gap tween exiting the kernel and the location in user code where flash read protection is enabled when someone may gain access to the flash.
revision 1 of the kernel, an extra step is required to ensure the user flash space is always protected. for 128kB parts, the user must set flash address 0x1FFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 e kernel will read this flash location and only enable the Serial Wire interface if the flash location does not contain this value. the current D30 parts, the kernel always enables the serial wire interface on exiting the kernel. Therefore, there is a short time gap
revision 1 of the kernel, an extra step is required to ensure the user flash space is always protected. For 128kB parts, the user must set flash address 0x1FFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the user must set flash address 0xFFFEC = 0x16032010 as well as set FEECON1.0=0 for 64kB parts, the

Supporting Documents None

	For questions on this PCN, send	email to the	regional contacts below or co	ntact your local ADI	sales representative	
mericas:	PCN_Americas@analog.com	Europe:	PCN_Europe@analog.com	Japan:	PCN_Japan@analog.com	
				Rest of Asia:	PCN ROA@analog.com	

Appendix A - Affected ADI Models Added Parts On This Revision - Product Family / Model Number (4)					

Appendix B - Revision History					
Rev	Publish Date	Effectivity Date	Rev Description		
Rev	28-Nov-2012	28-Nov-2012	Initial Release		

Analog Devices, Inc.

DocId:2193 Parent DocId:None Layout Rev:7