

PIN BUSBAR SHOCKPROOF, 10 SQMM 3-PHASE,  
1016 MM LONG CAN BE CUT, WITHOUT END CAPS




Figure similar

Model		
product brand name		SENTRON
Product designation		Pin busbar
<b>Design of the product</b>		10mm <sup>2</sup> 3PH L1016mm
<b>Busbar design</b>		laminated

General technical data		
<b>Surface processing / tin-plated</b>		No

Main circuit		
Operating current / Rated value	A	63

Product details		
Product property / flexible		Yes

Mechanical Design		
<b>Width</b>	mm	14.5
<b>Length</b>	mm	1 016
Thickness / of busbar	mm	17.5
Material / of the busbar		SF-Cu F 24

General Product Approval	Declaration of Conformity	other
		<a href="#">other</a>



[other](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5ST3740>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5ST3740/all>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=5ST3740](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5ST3740)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>



<sup>1)</sup> Pin spacings in MW (Modular widths, 1 MW = 18 mm).

last modified:

11.03.2015