STATSHIELD® METAL-OUT SERIES

Specifications: Standard Document

Meets Requirements of: ANSI/ESD S541 (ANSI/ESD S20.20)

ANSI/ESD S11.4

ESD Protective Packaging Level 3 Technical Requirements



Typical Values Test Procedures/Method

Surface Resistance: Outer Surface Inner Surface Discharge Shielding Charge Generation

 1×10^4 to $< 1 \times 10^8$ ohms ANSI/ESD STM11.11 1×10^4 to $< 1 \times 10^{11}$ ohms ANSI/ESD STM11.11 <20 nJ ANSI/ESD STM11.31, EIA 541 Modified Incline Plane Teflon: -0.03 nC/sq. in. Quartz: +0.10 nC/sq. in. Modified Incline Plane

Capacitance Probe (to dissipate 1 KV) <30 volts ANSI/EIA-541/Appendix E, 1 kV Discharge

Physical Properties:

Film Thickness Nominal 3.0 mil (0.07mm) ±10% Width (Inside Dimensions) Nominal -0" / + 0.250" Length (Inside Dimensions) Nominal + 0 125" **Light Transmission** 40% (Tobias) Puncture Resistance >10 lbs >10 lbs/in.

ASTM D-1003 MIL-STD-3010, 2065 375°F, 1/2 sec 60 psi

MIL-STD-3010, 1003

Pass Not detected MIL-STD-3010. M3005 FTIR

Pass

IPC-TM-650 2.4.1

Date & Lot Code

Printed for QC

Traceablility

Soft Fold Bottom

Heat Seal Non-corrosive Silicone

Marking Adhesion

ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

1. Low charge generation

2. Dissipative or conductive materials for intimate contact

3. A structure that provides electrostatic discharge shielding."

RoHS, REACH and Conflict Minerals Statement

See the Desco Industries RoHS, REACH, and Conflict Minerals Statement: Desco.com/pdf/REACHRoHSConflictMinerals-Desco Bags.pdf

See the Desco Limited Warranty:

Desco.DescoIndustries.com/Limited-Warranty.aspx

Statshield[®] and Statfree[®] are Registered Trademarks of Desco Industries Inc.

For product listing, Click **HERE** See Bag Selection Chart Click HERE



Made in the United States of America

of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades Desco's bags are recyclable

Mixed Unsortable Plastic Scrap Mixed unsortable plastic scrap shall contain assorted plastics

Statshield® bags are packaged 100 per package in an oversized shielding bag. See Shielding Bag Storage at TB-7057.

Specifications and procedures subject to change without notice.

STATSHIELD® BAG, SHIELDING, METAL-OUT CONSTRUCTION, ZIPPER, 3.0 MIL (0.07mm)



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com

PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407

PHONE (781) 821-8370

DRAWING NUMBER 13205

DATE: June 2019

Low Charging Clear Zipper

Opening

STATSHIFI D Static Shielding Bad

(inches)

Side Weld Seals 3/8 in. (±0.10)

Lip 1 in. (±0.125)

Shielding Layer

Polyester Layer Low Charging Static

Low Charging Static

Dissipative Proprietary

Dissipative Proprietary Inner Polyethylene Layer

High Performance Static Dissipative Abrasion Resistant Coating

Lip

Lenath

(inches)

Weld Seal