SIEMENS

Data sheet

Product type designation	Antenna ANT794-3M FLAT ANTENNA FOR GSM - (2G) NETWORKS, TRIPLE-BAND WITH 900 / 1800 / 1900 MHZ; INDEPENDENT MOUNTING FOR
	INSIDE AND OUTSIDE; 1.2 M CONNECTING CABLE FIXED PERMANENTLY WITH ANTENNA; SMA CONNECTOR; INCL. MOUNTING BONDING PAD
Suitability for operation	for indoor and outdoor applications
Wireless frequencies	
Type of mobile network / is supported	GSM
Operating frequency	900 MHz, 1800 MHz, 1900 MHz
Electrical data	
Radiation characteristic	directional
Antenna gain	0 dB
Standing wave ratio (VSWR) / maximum	1.5
Type of electrical connection / of the antenna	SMA Connector
Design of plug-in connection	male
Transmit power / maximum	10 W
Mechanical data	
Material	
• of outer shell	ABS Polylac PA-765, light gray (RAL 7035)
Permitted ambient conditions	
Ambient temperature	
 during operation 	-40 +75 °C
Protection class IP	IP64
Design, dimensions and weight	
Width	70.5 mm
Height	20.5 mm
Depth	146.5 mm
Net weight	130 g

Mounting type	screw fixing	
Cable length / of antenna cable	1.2 m	
Standards, specifications, approvals		
Certificate of suitability		
RoHS conformity	Yes	
Further Information / Internet Links		
Internet-Link		
 to website: Selector SIMATIC NET 	http://www.siemens.com/snst	
SELECTION TOOL		
 to website: Industrial communication 	http://www.siemens.com/simatic-net	
• to website: Industry Mall	https://mall.industry.siemens.com	
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog	
 to website: Image database 	http://automation.siemens.com/bilddb	
 to website: CAx Download Manager 	http://www.siemens.com/cax	
 to website: Industry Online Support 	https://support.industry.siemens.com	
last modified:	09.03.2015	