

# SAFETY DATA SHEET

## 89216 AEROSOL PAINT REMOVER 400ML

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** 89216 AEROSOL PAINT REMOVER 400ML  
**Product number** 003543000005

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint remover.  
**Uses advised against** Use only for intended applications.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** James Briggs Ltd.  
Salmon Fields  
Royton  
Oldham  
Lancashire  
OL2 6HZ  
0161 627 0101  
sds@jamesbriggs.co.uk

#### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 161 620 5400

### SECTION 2: Hazards identification


#### 2.1. Classification of the substance or mixture

##### Classification (SI 2019 No. 720)

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** Eye Dam. 1 - H318  
**Environmental hazards** Not Classified

#### 2.2. Label elements

##### Hazard pictograms



**Signal word** Danger

**Hazard statements** H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated.  
H318 Causes serious eye damage.

## 89216 AEROSOL PAINT REMOVER 400ML

<b>Precautionary statements</b>	P102 Keep out of reach of children.
	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211 Do not spray on an open flame or other ignition source.
	P251 Do not pierce or burn, even after use.
	P261 Avoid breathing vapour/ spray.
	P271 Use only outdoors or in a well-ventilated area.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313 If eye irritation persists: Get medical advice/ attention.
	P302+P352 IF ON SKIN: Wash with plenty of water.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
P501 Dispose of contents/ container in accordance with local regulations.	

**Supplemental label information** EUH066 Repeated exposure may cause skin dryness or cracking.

**Contains** 1,3-dioxolane

**Supplementary precautionary statements** P332+P313 If skin irritation occurs: Get medical advice/ attention.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>1,3-dioxolane</b>	<b>30- &lt; 60%</b>
CAS number: 646-06-0	EC number: 211-463-5
<b>Classification</b>	
Flam. Liq. 2 - H225	
Eye Dam. 1 - H318	
<b>Dimethyl ether</b>	<b>30- &lt; 60%</b>
CAS number: 115-10-6	EC number: 204-065-8
<b>Classification</b>	
Flam. Gas 1A - H220	
Press. Gas (Liq.) - H280	
<b>Acetone</b>	<b>10 - &lt;30%</b>
CAS number: 67-64-1	EC number: 200-662-2
EUH066	
<b>Classification</b>	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	



## 89216 AEROSOL PAINT REMOVER 400ML

**Suitable extinguishing media** The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Vapours may form explosive mixtures with air.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Take precautionary measures against static discharges.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Not considered to be a significant hazard due to the small quantities used.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Provide adequate ventilation. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## **SECTION 7: Handling and storage**

## 89216 AEROSOL PAINT REMOVER 400ML

### 7.1. Precautions for safe handling

#### **Usage precautions**

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. The product is flammable. Avoid exposing aerosol containers to high temperatures or direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Do not expose to temperatures exceeding 50°C/122°F. Avoid inhalation of vapours and spray/mists. Avoid contact with eyes.

#### **Advice on general occupational hygiene**

Good personal hygiene procedures should be implemented. Wash contaminated skin thoroughly after handling. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash after use and before eating, smoking and using the toilet.

### 7.2. Conditions for safe storage, including any incompatibilities

#### **Storage precautions**

Store away from incompatible materials (see Section 10). Keep away from oxidising materials, heat and flames. Store in a cool and well-ventilated place. Protect from sunlight. Keep containers upright. Protect containers from damage. Do not expose to temperatures exceeding 50°C/122°F. Do not store near heat sources or expose to high temperatures. Store in accordance with national regulations.

#### **Storage class**

Chemical storage. Aerosol containers and lighters

### 7.3. Specific end use(s)

#### **Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

## **SECTION 8: Exposure controls/Personal protection**

### **8.1. Control parameters**

#### Occupational exposure limits

##### **Dimethyl ether**

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m<sup>3</sup>

##### **Acetone**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

##### **Paraffin waxes and Hydrocarbon waxes**

Long-term exposure limit (8-hour TWA): WEL 2 mg/m<sup>3</sup> fume

Short-term exposure limit (15-minute): WEL 6 mg/m<sup>3</sup> fume

WEL = Workplace Exposure Limit.

#### **1,3-dioxolane (CAS: 646-06-0)**

#### **DNEL**

Workers - Inhalation; Long term systemic effects: 37.7 mg/m<sup>3</sup>

Workers - Dermal; Long term systemic effects: 0.04 mg/kg/day

General population - Inhalation; Long term systemic effects: 45.2 mg/m<sup>3</sup>

General population - Dermal; Long term systemic effects: 0.04 mg/kg/day

General population - Oral; Long term systemic effects: 0.63 mg/kg/day

## 89216 AEROSOL PAINT REMOVER 400ML

<b>PNEC</b>	- Fresh water; 19.7 mg/l
	- marine water; 1.97 mg/l
	- Intermittent release; 0.95 mg/l
	- STP; 1 mg/l
	- Sediment (Freshwater); 77.7 mg/kg
	- Sediment (Marinewater); 7.77 mg/kg
	- Soil; 2.62 mg/kg

### Dimethyl ether (CAS: 115-10-6)

<b>DNEL</b>	Workers - Inhalation; Long term systemic effects: 1894 mg/m <sup>3</sup>
	General population - Inhalation; Long term systemic effects: 471 mg/m <sup>3</sup>

<b>PNEC</b>	- Fresh water; 0.155 mg/l
	- marine water; 0.016 mg/l
	- STP; 160 mg/l
	- Sediment (Freshwater); 0.681 mg/kg
	- Sediment (Marinewater); 0.069 mg/kg
	- Soil; 0.045 mg/kg

### Acetone (CAS: 67-64-1)

<b>DNEL</b>	Workers - Inhalation; Long term systemic effects: 1210 mg/m <sup>3</sup>
	Workers - Inhalation; Short term systemic effects: 2420 mg/m <sup>3</sup>
	Workers - Dermal; Long term systemic effects: 186 mg/kg/day
	General population - Inhalation; Long term systemic effects: 200 mg/m <sup>3</sup>
	General population - Dermal; Long term systemic effects: 62 mg/kg/day
	General population - Oral; Long term systemic effects: 62 mg/kg/day

<b>PNEC</b>	- Fresh water; 10.6 mg/l
	- marine water; 1.06 mg/l
	- STP; 100 mg/l
	- Sediment (Freshwater); 30.4 mg/kg
	- Sediment (Marinewater); 3.04 mg/kg
	- Soil; 29.5 mg/kg

### 2,6-di-tert-butyl-4-(4,6-bis(octylthio)-1,3,5-triazin-2-ylamino)phenol (CAS: 991-84-4)

<b>DNEL</b>	Workers - Inhalation; Long term systemic effects: 3 mg/m <sup>3</sup>
	Workers - Inhalation; Short term systemic effects: 3 mg/m <sup>3</sup>
	Workers - Inhalation; Long term local effects: 3 mg/m <sup>3</sup>
	Workers - Dermal; Long term systemic effects: 130 mg/kg/day
	General population - Dermal; Long term systemic effects: 65 mg/kg/day
	General population - Oral; Long term systemic effects: 6.5 mg/kg/day

<b>PNEC</b>	- STP; 1 mg/l
-------------	---------------

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

## 89216 AEROSOL PAINT REMOVER 400ML

<b>Eye/face protection</b>	Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses. Personal protective equipment that provides appropriate eye and face protection should be worn.
<b>Hand protection</b>	To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
<b>Other skin and body protection</b>	Wear appropriate clothing to prevent repeated or prolonged skin contact.
<b>Hygiene measures</b>	Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.
<b>Respiratory protection</b>	Ensure all respiratory protective equipment is suitable for its intended use and is 'UKCA'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges suitable for intended use should be used. Full face mask respirators with replaceable filter cartridges suitable for intended use should be used. Half mask and quarter mask respirators with replaceable filter cartridges suitable for intended use should be used.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Odour</b>	Organic solvents.
<b>Initial boiling point and range</b>	-24.8°C (DME)
<b>Flash point</b>	-41°C (DME)
<b>Upper/lower flammability or explosive limits</b>	3.3 - 26.2% (V) (DME)
<b>Vapour pressure</b>	513.29kPa (DME)
<b>Auto-ignition temperature</b>	226°C (DME)

#### 9.2. Other information

<b>Volatility</b>	Volatile.
-------------------	-----------

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
-------------------	--

#### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
------------------	---

#### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	The following materials may react strongly with the product: Oxidising agents.
---	--

#### 10.4. Conditions to avoid

## 89216 AEROSOL PAINT REMOVER 400ML

**Conditions to avoid** Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised container: may burst if heated Avoid heat, flames and other sources of ignition. Avoid the following conditions: Freezing.

### 10.5. Incompatible materials

**Materials to avoid** No specific requirements are anticipated under normal conditions of use.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicological effects** Information given is based on data of the components. The blended product has not been tested. No data is available for the mixture.

**Inhalation** Gas or vapour may irritate the respiratory system. May cause nausea, headache, dizziness and intoxication. Vapour may irritate respiratory system/lungs.

**Ingestion** Due to the physical nature of this product, it is unlikely that ingestion will occur. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May cause chemical burns in mouth, oesophagus and stomach. May cause discomfort if swallowed. May cause stomach pain or vomiting.

**Skin contact** Repeated exposure may cause skin dryness or cracking.

**Eye contact** May cause eye irritation. May cause serious eye damage.

**Route of exposure** Inhalation Ingestion Skin and/or eye contact

## SECTION 12: Ecological information

### 12.1. Toxicity

**Toxicity** The product is not believed to present a hazard due to its physical nature.

### 12.2. Persistence and degradability

**Persistence and degradability** Volatile substances are degraded in the atmosphere within a few days. The other substances in the product are not expected to be readily biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** Bioaccumulation is unlikely to be significant because of the low water-solubility of this product. Exposure to aquatic environment unlikely.

### 12.4. Mobility in soil

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product hardens to a solid, immobile substance.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current UK criteria.

### 12.6. Other adverse effects

**Other adverse effects** The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.



## 89216 AEROSOL PAINT REMOVER 400ML

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

<b>General information</b>	The generation of waste should be minimised or avoided wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Dispose of waste product or used containers in accordance with local regulations
<b>Disposal methods</b>	Do not empty into drains. Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
<b>Waste class</b>	16-05-04

### SECTION 14: Transport information

#### 14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

#### 14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ICAO packing group	None
ADN packing group	None

#### 14.5. Environmental hazards

## 89216 AEROSOL PAINT REMOVER 400ML

### Environmentally hazardous substance/marine pollutant

No.

#### 14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits. The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
----------------------	--

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### Inventories

##### EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

### SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
	ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
	RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
	IATA: International Air Transport Association.
	ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
	IMDG: International Maritime Dangerous Goods.
	CAS: Chemical Abstracts Service.
	ATE: Acute Toxicity Estimate.
	LC50: Lethal Concentration to 50 % of a test population.
	LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).
	EC <sub>50</sub> : 50% of maximal Effective Concentration.
	PBT: Persistent, Bioaccumulative and Toxic substance.
	vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations and acronyms	Aerosol = Aerosol
---	-------------------

Key literature references and sources for data	Source: European Chemicals Agency, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a>
--	--

Classification procedures according to SI 2019 No. 720	Aerosol 1 - H222, H229: : Expert judgement.
--	---

**89216 AEROSOL PAINT REMOVER 400ML**

<b>Revision date</b>	17/11/2021
<b>Revision</b>	4
<b>Supersedes date</b>	24/06/2021
<b>SDS number</b>	7288
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.