Note: This datasheet may be out of date Please download the latest datasheet of DLW32MH201XK2#from the official website of Murata Manufacturing

https://www.murata.com/en-eu/products/productdetail?partno=DLW32MH201XK2%23

DLW32MH201XK2#

"#" indicates a package specification code.










< List of part numbers with package codes > DLW32MH201XK2B DLW32MH201XK2L



Appearance & Shape







- 1. Suitable for noise suppression at car area networks.
- 2. High common mode impedance at high frequency range. So it is suitable for noise suppression through wide frequency
- 3. Wide operating temperature range meet automotive application. (-40 to +125 degrees C)



Automotive
Usage

Powertrain/Safety



Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	500
L	180mm Embossed Tape	1500

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ DLW32MH201XK2\# from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ $\underline{Co., Ltd.} \\ https://www.murata.com/en-eu/products/productdetail?partno=DLW32MH201XK2\%23$

DLW32MH201XK2#

"#" indicates a package specification code.

Note: This datasheet may be out of date



Shape	SMD
Size Code (in mm)	3225
Size Code (in inch)	1210
Length	3.2mm
Length Tolerance	±0.2mm
Width	2.5mm
Width Tolerance	±0.2mm
Thickness	2.5mm
Thickness Tolerance	max.
Rated Current	70mA
Rated Voltage	50Vdc
Withstanding Voltage	125Vdc
DC Resistance(max.)	4.8Ω
DC Resistance	4.0Ω±20%
Insulation Resistance(min.)	10ΜΩ
Operating Temperature Range	-40°C to 125°C
Mass(typ.)	0.072g

Number of Circuit	1		
Common Mode Inductance	200μH-20%/+50% (at 0.1MHz)		
Operating Temperature Range(Self- temperature rise is included)	No		

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/08/21


^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


https://www.murata.com/en-eu/products/productdetail?partno=DLW32MH201XK2%23

DLW32MH201XK2#

"#" indicates a package specification code.








Impedance-Frequency Characteristics

Impedance-Frequency Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/08/21