

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: **0340801003**
Status: **Active**
Overview: MX150 Sealed and Unsealed Connector System
Description: MX150 Cable Seal Male Terminal, Tin Plating, 22 AWG, Left Reel Payoff

Documents:

Drawing (PDF)	Test Summary TS-34080-001-001 (PDF)
Product Specification PS-34083-002-001 (PDF)	Datasheet (PDF)
Application Specification AS-34080-001-001 (PDF)	RoHS Certificate of Compliance (PDF)
Packaging Specification 313025040-000 (PDF)	

General

Product Family	Crimp Terminals
Series	<u>34080</u>
Application	Power, Wire-to-Board, Wire-to-Wire
Comments	Left Reel Payoff
Crimp Quality Equipment	Yes
Overview	<u>MX150 Sealed and Unsealed Connector System</u>
Product Name	MX150
UPC	883906369323

Physical

Gender	Male
Grip Code	22
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	0.363/g
Packaging Type	Reel
Plating min - Mating	0.508µm
Plating min - Termination	0.508µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	1.70mm max.
Wire Size AWG	22
Wire Size mm ²	0.50

Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	14V DC

Solder Process Data

Lead-free Process Capability	N/A
------------------------------	-----

Material Info

Reference - Drawing Numbers

Application Specification	AS-34080-001-001
Packaging Specification	313025040-000
Product Specification	PS-34083-002-001
Sales Drawing	SD-34080-001-001
Test Summary	TS-34080-001-001



Series image - Reference only

EU ELV

Compliant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2021)4569-DC (8
July 2021)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Compliant

Not Contained

Search Parts in this Series

34080 Series

Use With

34675 MX150 2 Way Inline Male Assembly with TPA, 34091 MX150 1.50mm 3 Way Single Row Cable Seal

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
-------------	-----------

FA2 Mechanical	<u>638083100</u>
----------------	------------------

Applicator for MX150 Terminals, 22 AWG, 0.35mm², 0.50mm² Wire

FA2 Pneumatic Feed	<u>638083110</u>
--------------------	------------------

Crimp Applicator for MX150 22 Grip Wire Seal Blade Terminals

Hand Crimp Tool for [638199300](#)
Cable Seal Crimp
Terminals

This document was generated on 10/06/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION