


Isolierte Aderendhülsen nach DIN, mit Easy Entry

Nennquerschnitt mm ²	Art.-Nr.	Farbe	Hinweis	Abmessung mm					Gewicht/ 1000 St. ~ kg	VE/St.
				d1	d3	l1	l2	s1		
16	47712	■		5,8	9,6	24	12	0,20	0,650	100
	47718	■		5,8	9,6	28	18	0,20	0,800	100
25	47816	■		7,3	12,0	30	16	0,20	1,600	50
	47818	■		7,3	12,0	30	18	0,20	1,700	50
	47822	■		7,3	12,0	36	22	0,20	2,000	50
35	47916	■		8,3	13,5	30	16	0,20	1,900	50
	47918	■		8,3	13,5	30	18	0,20	2,100	50
	47925	■		8,3	13,5	39	25	0,20	2,500	50
50	48020	■		10,3	16,0	36	20	0,30	3,300	50
	48025	■		10,3	16,0	40	25	0,30	3,600	50
70	48121	■	*	13,5	17,2	37	21	0,40	4,620	25
95	48225	■	*	14,5	19,2	44	25	0,40	6,000	25
120	48327	■	*	16,7	21,4	48	27	0,45	7,850	25
150	48432	■	*	19,5	25,0	58	32	0,50	12,330	25

Isolierte Aderendhülsen nach DIN mit Easy Entry, Farbcode 1



- ▶ Für fein- und feinstdrähtige Leiter z.B. nach DIN EN 60228 Klasse 5 und 6
- ▶ Easy-Entry Isolierung für spleissfreie Kabeleinführung
- ▶ Halogenfrei



Eigenschaften

- Nach DIN 46228 Teil 4 (0,5 - 50 mm²)
- Temperaturbeständigkeit: bis 105° C



Werkstoff

- Cu-DHP
- Kunststoff: Polypropylen



Oberfläche

- Galvanisch verzinkt zum Schutz gegen Korrosion

Verarbeitungshinweise

- Werkzeug: siehe Seite 148




































Zusatzinformationen

- * = nicht genormt
- ** = Stückzahl in einem Beutel

Nennquerschnitt mm ²	Art.-Nr.	Farbe	Hinweis	Abmessung mm					Gewicht/ 1000 St. ~ kg	VE/St.
				d1	d3	l1	l2	s1		
0,14	166GR	■	*	0,7	2,5	10,0	6	0,15	0,035	1000
	166GRL	■	*	0,7	2,5	12,0	8	0,15	0,040	1000
0,25	167H	■	*	0,8	2,5	10,0	6	0,15	0,045	1000
	167HL	■	*	0,8	2,5	12,0	8	0,15	0,050	1000
0,34	168T	■	*	0,8	2,5	10,0	6	0,15	0,045	1000
	168TL	■	*	0,8	2,5	12,0	8	0,15	0,050	1000
0,5	1690K	■		1,0	3,1	12,0	6	0,15	0,070	1000
	1690	■		1,0	3,1	14,0	8	0,15	0,070	1000
	GR1690	■	**	1,0	3,1	14,0	8	0,15	0,070	500
	1690H	■		1,0	3,1	16,0	10	0,15	0,085	1000

Fortsetzung nächste Seite

Isolierte Aderendhülsen nach DIN mit Easy Entry, Farbcode 1

Nennquerschnitt mm ²	Art.-Nr.	Farbe	Hinweis	Abmessung mm					Gewicht/ 1000 St. ~ kg	VE/St.
				d1	d3	l1	l2	s1		
0,75	170WK			1,2	3,3	12,0	6	0,15	0,080	1000
	170W			1,2	3,3	14,0	8	0,15	0,080	1000
	GR170W		**	1,2	3,3	14,0	8	0,15	0,080	500
	170WH			1,2	3,3	16,0	10	0,15	0,100	1000
	170WL			1,2	3,3	18,0	12	0,15	0,105	1000
1	171GK			1,4	3,5	12,0	6	0,15	0,090	1000
	171G			1,4	3,5	14,0	8	0,15	0,100	1000
	GR171G		**	1,4	3,5	14,0	8	0,15	0,100	500
	171GH			1,4	3,5	16,0	10	0,15	0,120	1000
	171GL			1,4	3,5	18,0	12	0,15	0,125	1000
1,5	172RK			1,7	4,0	12,0	6	0,15	0,105	1000
	172RO			1,7	4,0	14,0	8	0,15	0,110	1000
	GR172RO		**	1,7	4,0	14,0	8	0,15	0,110	500
	172RH			1,7	4,0	16,0	10	0,15	0,130	1000
	172RM			1,7	4,0	18,0	12	0,15	0,140	1000
2,5	172RL			1,7	4,0	24,0	18	0,15	0,190	1000
	173B			2,2	4,7	14,0	8	0,15	0,150	1000
	GR173B		**	2,2	4,7	14,0	8	0,15	0,150	500
	173BH			2,2	4,7	18,0	12	0,15	0,200	1000
4	173BL			2,2	4,7	24,0	18	0,15	0,250	1000
	174GR			2,8	5,4	17,0	10	0,20	0,210	100
	174GRH			2,8	5,4	20,0	12	0,20	0,250	100
6	174GRL			2,8	5,4	26,0	18	0,20	0,320	100
	175S			3,5	6,9	20,0	12	0,20	0,350	100
10	175SL			3,5	6,9	26,0	18	0,20	0,460	100
	176E			4,5	8,4	22,0	12	0,20	0,450	100
16	176EL			4,5	8,4	28,0	18	0,20	0,650	100
	177GR			5,8	9,6	24,0	12	0,20	0,650	100
25	177GRL			5,8	9,6	28,0	18	0,20	0,800	100
	178BR			7,3	12,0	30,0	16	0,20	1,600	50
35	178BRL			7,3	12,0	36,0	22	0,20	2,000	50
	179B			8,3	13,5	30,0	16	0,20	1,900	50
50	179BL			8,3	13,5	39,0	25	0,20	2,500	50
	1800			10,3	16,0	36,0	20	0,30	3,300	50
	1800L			10,3	16,0	40,0	25	0,30	4,000	50