

## Motor operator 208-240 VAC/DC

Part no. IZMX-M16-230AD-1 Article no. 184254 Catalog No. 67C3048G35



**Delivery programme** 

		Accessories
		Remote switching
		Motor operator
		The motor automatically tensions the spring force storage mechanism for remote or local actuation. Retrofitting kit
Actuations/ minute		3
		Please note - the circuit-breaker's switching frequency = 60/h
U <sub>s</sub>	V	220 - 240 V AC 50/60 Hz 220 - 250 V DC
x U <sub>S</sub>	Factor	0,85 - 1,1
In	Α	1
In	Α	10
AC/DC	VA/W	280 AC / 150 DC
AC/DC	VA/W	4
		IZMX16 INX16
		A signaling switch for the labeled "Spring-operated stored energy mechanism tensioned" message is included as standard.
	minute  Us x Us In AC/DC	winute           Us         V           x Us         Factor           In         A           In         A           AC/DC         VA/W

## **Technical data**

Rated control voltage	U <sub>s</sub>	V	220 - 240 V AC 50/60 Hz 220 - 250 V DC
Necessary time required for charging the spring-operated stored energy mechanism at 1 x $\rm U_{\rm S}$			4 s AC 50/60 Hz 4 s DC
Rated operational current	In	Α	1 A AC 50/60 Hz 1 A DC
Starting current		Α	10 A AC 50/60 Hz 10 A DC
Power consumption			280 VA AC 50/60 Hz 280 W DC

## Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

## **Technical data ETIM 6.0**

Low-voltage industrial components (EG000017) / Motor operator for power circuit-breaker (EC001030)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Electrical drive for circuit breakers (ecl@ss8.1-27-37-04-12 [AKF010010])

[AKF010010])				
Type of switch drive		Motor drive		
Rated control supply voltage Us at AC 50HZ	V	220 - 240		
Rated control supply voltage Us at AC 60HZ	V	220 - 240		
Rated control supply voltage Us at DC	V	220 - 250		
Voltage type for actuating		AC/DC		