

Twin Cables

Figure 8 - 7 / 0.25mm

multicomp PRO



Feature

Plain annealed copper connecting wire in a twin, figure '8' PVC insulated with one core ribbed for identification.

Specifications for (2X463 GRY & 2X463 WHI)

Conductors	: (0.34 mm ²) 7 / 0.25 mm
Construction	: 2 × conductors laid parallel. One leg incorporates a polarity rib
Temperature Rating	: -15°C to +70°C
Overall Diameter	: 1.4mm × 2.8mm
Nominal Wall Thickness	: 0.32mm
Related Specifications	: BS 6360 conductors in insulated cables and cords BS 7655 insulating and sheathing materials for cables

Specifications for (2X463 BLK)

Description	: 7 / 0.25mm BC × 2C 2.1 × 4.2mm (0.34 mm ²)
Conductor	: 7 / 0.25 ±0.003mm BC × 2C
Stranding	: Nominal diameter 0.76mm
Insulation	: Material : PVC / Colour : Black Min. thickness 0.55mm / nominal thickness 0.65mm Spark voltage : 3,000V AC
Physical Properties	: Sheath elongation (%) : ≥100 / sheath tensile strength (N / mm ²) : ≥8
Electrical Properties	: Inner conductor maximum DC resistance : 55Ω / km 20°C
Remarks	: BC = Bare Copper

Specification Table

Voltage Rating (V rms)	Current Rating (A)	Reel Length (m)	Colour	Part Number
60	1	100	Black	2X463 BLK
			Grey	2X463 GRY
			White	2X463 WHI

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO