
# multicomp PRO




## **Electrical Character**

Hi-POT	: DC300V 10ms
Insulation Resistance	: 5MΩ Min.
Contact Resistance	: 2Ω Max.
100% Open and Short	Test

### Diagram







Dimensions : Millimetres

No.	Part Name	Description		
1.	Connector 1	USB2.0 Micro B Type Female Pin G/F, Shell Plated Nickel		
2.	Connector 2	USB3.1 C Type Male Pin G/F, Shell Plated Nickel		
3.	PCB	USB C Male to Micro B/F PCBA		
4.	Inner Mold	LD-PE		
5.	Over Mold	PVC 70Pa Black		

#### PIN ASSIGNMENT

	SINGNAL	P1	COLOUR	Conn.2	SINGNAL
22%	VBUS	A4,B4,A9,B9	RED	1	VBUS
	DN1	Α7	WHITE ()	2	D-
10k.0±5%	DP1	A6	<sub>green</sub> V	3	D+
-	GND	A1,B1,A12,B12	BLACK	5	GND
	CC	A5			
	SHIELD	SHELL	SHIELD	SHELL	SHELL

### Part Number Table

Description	Part Number	
USB 2.0 Micro B Female to USB C Male Adapter	MC000994	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

