

SEK-18 SV MA LP STR29 06P PL2



| Part number | 09 18 506 6324 |
|--------------------|-------------------------------------|
| Specification | SEK-18 SV MA LP STR29 06P PL2 |
| HARTING eCatalogue | https://b2b.harting.com/09185066324 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Connectors |
|----------------------------|-----------------|
| Series | SEK Low-profile |
| Element | Male connector |
| Description of the contact | Straight |

Version

| Termination method | Wave soldering termination |
|--------------------|----------------------------|
| Connection type | PCB to cable PCB to PCB |
| Number of contacts | 6 |
| Termination length | 2.9 mm |

Technical characteristics

| Contact rows | 2 |
|------------------------------------|---------------------------|
| Contact spacing (termination side) | 2.54 mm |
| Rated current | 1 A |
| Insulation resistance | >10 ⁹ Ω |
| Contact resistance | ≤20 mΩ |
| Limiting temperature | -55 +125 °C |
| Insertion force | ≤12 N |
| Withdrawal force | ≤12 N |
| Performance level | 2 acc. to IEC 60603-13 |
| Mating cycles | ≥250 |



Technical characteristics

| Test voltage U _{r.m.s.} | 1 kV |
|----------------------------------|------------------------|
| Isolation group | IIIa (175 ≤ CTI < 400) |

Material properties

| Material (insert) | Thermoplastic resin (PBT) |
|---|---|
| Colour (insert) | Grey |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Noble metal over Ni Mating side Sn over Ni Termination side |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Antimony trioxide Lead Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

| Specifications | IEC 60603-13 |
|------------------------|--|
| UL / CSA | UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079 |
| Railway classification | F3/I3 |

Commercial data

| Packaging size | 100 |
|--------------------------------|---------------|
| Net weight | 2 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| GTIN | 5713140026117 |



Commercial data

ETIM EC002637

eCl@ss 27460201 PCB connector (board connector)

Cross section of solder termination

