

# DATASHEET

## QuickFix Water resistant

### 1. Identification of the substances/preparation and of the company/undertaking

|                                  |                                  |
|----------------------------------|----------------------------------|
| Date issued                      | 06.04.2006                       |
| Revision                         | 06.04.2006                       |
| Product name                     | Quick Fix Water resistant        |
| Index no.                        | Version 1.0                      |
| Use of the substance/preparation | Plaster QuickFix Water resistant |

#### Producer

|                |                                                     |
|----------------|-----------------------------------------------------|
| Company name   | Plum A/S                                            |
| Postal address | Frederik Plums Vej 2                                |
| Postcode       | 5610                                                |
| Place name     | Assens                                              |
| Country        | Danmark                                             |
| Tel.           | 0045 6471 2112                                      |
| Fax            | 0045 6471 21 25                                     |
| E-mail         | <a href="mailto:info@plum.dk">info@plum.dk</a>      |
| Website        | <a href="http://www.plum.dk">http://www.plum.dk</a> |

### 2. Backing

|                              |                   |
|------------------------------|-------------------|
| Composition                  | Polyethylene film |
| Colour                       | Pink              |
| Weight (g/m <sup>2</sup> )   | 62-69             |
| Thickness (μm <sup>2</sup> ) | 70                |

### 3. Adhesive

|                            |                                |
|----------------------------|--------------------------------|
| Composition                | Hypoallergenic acrylic polymer |
| Weight (g/m <sup>2</sup> ) | 28-36                          |

### 4. Coated backing

|                                             |                        |
|---------------------------------------------|------------------------|
| Weight (g/m <sup>2</sup> )                  | 90-105                 |
| Adhesion to steel by peeling at 180° (N/cm) | >1,6                   |
| M.V.T.R. (g/m <sup>2</sup> /24h/37°C)       | >500 (microperforated) |
| Water resistant                             | yes                    |

### 5. Absorbent pad

|                                     |                                              |
|-------------------------------------|----------------------------------------------|
| Total weight (g/m <sup>2</sup> )    | 100-160                                      |
| Absorbency (g/100 cm <sup>2</sup> ) | 9-16                                         |
| Absorbent layer                     | Viscose, polypropylene/polyethylene nonwoven |
| Colour                              | White                                        |
| Antiadherent layer                  | Microperforated PE film                      |

### 6. Liner

#### Monosiliconated paper

|                            |       |
|----------------------------|-------|
| Weight (g/m <sup>2</sup> ) | 57-63 |
| Colour                     | White |

QuickFix Water resistant

7. Primary packing

Individual pouch: paper + clear film

|                                  |                                           |
|----------------------------------|-------------------------------------------|
| Paper composition                | Cold sealed paper                         |
| Paper weight (g/m <sup>2</sup> ) | 40-50                                     |
| Film composition                 | Polyethylene terephthalate / polyethylene |
| Film weight (g/m2)               | 52-67                                     |