

TECHNICAL DATASHEET

G-PANO 2 SAFETY SPECTACLES

Update: 04/06/2021

Reference	EAN	Product
888385 / 13325904	3660338412714	Amber Lens

Description

Length and angle adjustment temples with extended wraparound lens for perfect fit and clear vision. Weight: 28 g.

Lens Colour: Amber Temple Colour: Black Temple: Nylon Lens: Polycarbonate Screw: Stainless Steel



Main assets

Adjustable temples. Improved resistance thanks to polycarbonate.

One-piece screen, curved shape, panoramic vision.

Ergonomic shape allowing an excellent maintenance of the equipment on the face and a wide field of vision.

Modern design! UV protection.

Anti-scratch and anti-fog coatings.

Applications

Protection against mechanical risks (projections of solids, chips, particles, shocks...), against UV rays. Grinding, industry, sport, laboratories, automotive assembly, etc.

Characteristics

Lens Base: 9 curve. Lens thickness: 2.2 mm.

Markings:

Frame: EN 166: 2001-FT

Amber lens: 1.F

Performance: Lens offers protection against low energy impacts at 45m/s (162 km/hour) The optical qualities of the lens comply with the requirements of optical class 1 (highest)

Working Environments: For use in good visibility conditions

Instructions & maintenance

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

Standard and certifications

EN166: 2001

UK CA

Packaging - Packed per pair / 10 pairs per box / 300 paires per case