Pocket Laser Tachometer



Features

- Contact or Non-Contact modes
- View display and target simultaneously
- Lightweight
- Operates up to 25 feet from target
- Use remote sensors

Ordering Information

<u>ltem</u>

PLT200 Kit

T-5 tape 12" Wheel

TTL input/output (3.5mm phono plug)

Description



Target

Part No.

6125-010

6125-011

6180-057

6180-070

6580-011

View Display and

The Pocket Laser Tach 200 (PLT200) is a digital, battery-powered portable optical tachometer, which operates up to 25 feet (8 meters) from a reflective target using a class 2 laser light source. The ergonomic design allows safe, direct line-of-sight viewing of both the target and the display at the same time, while providing a non-slip rubber surface for single hand operation.

Multifunction Tool

The PLT200 is a 32 function Tachometer/Rate meter, Totalizer/Counter and Timer (stopwatch), which is programmable in both Imperial and Metric rates. Includes two phono plug connectors for our optional Remote Contact Assembly (RCA) or remote sensors. The PLT200 also has a TTL compatible pulse output to trigger devices like vibration data collectors or stroboscopes. The KIT is supplied complete with a Remote Contact Assembly including concave and convex tips and a 10 cm linear speed wheel all in a latching carrying case. Sensors and input/output cable are optional.

PT-99 **Pocket Tachometer**



The Pocket Tach 99 (PT99) is a digital, battery-powered portable non-contact optical tachometer, which operates up to 36 inches from a reflective target using a bright red LED light source. The ergonomic design allows safe, direct line-of-sight viewing of both the rotating target and the display at the same time, while providing a non-slip rubber surface for single hand operation. The PT99 is the value-leader of the world-class Pocket Tach Series from Monarch.

Features

- 36 inch operating distance
- One hand operation
- LED light source
- Simple operation

Ordering Information		
Item	Description	Part No.
PT99	Tachometer with 12 inches of T-5 tape, batteries	6109-010

Tachometer, NIST Cert., batteries, 12 inches of T-5 tape

RCA with tips, linear speed wheel, 5 foot roll of T-5 tape

Remote Optical Sensor (LED) with 8' cable, 1/8" (3.5mm)

phone plug and 12 inches of T-5 tape Reflective tape 5' roll, 0.5" wide

with RCA (Remote Contact Assembly)

Tachometer, NIST Cert., batteries, latching carry case,

Specifications

Specifications

op conjugations	
Display:	5 Digits, 5 Alphanumeric LCD
Range:	5 to 99,999 RPM
Accuracy:	0.01% or ± 1 Digit
Resolution:	Auto ranging: 0.001 to 1 RPM Fixed: 1 Digit
Operating Range:	2" to 36" (5cm to 91.44cm), ± 45° from perpendicular
Memory:	Max, Min and Last
Power:	(2) "AA" 1.5Vdc batteries (60 hours)
Environmental:	5° to 40° C (40° to 105° F), 80% RH up to 31° C (88° F)
Dimensions:	6.92 x 2.4 x 1.6in (17.58 x 6.10 x 4.06cm)
Weight:	7 ounces (210 grams)