SIEMENS

Data sheet 6GT2398-1DA10

product type designation



antenna ANT 18 stainless steel, with antenna cable

SIMATIC RF200/RF300 antenna ANT 18 stainless steel; -25...+70 °C, IP65, thread M18x1, length 40 mm; with trailing antenna wire, both ends plug-in PUR, UL 758, length 3 m .

T: -			
HIQ	ure	sim	ııar

suitability for operation	RF250R / RF350R / RF350M
radio frequencies	
transmission frequency / rated value	13.56 MHz
electrical data	
type of electrical connection / of the antenna	M8, 4-pole (at supplied cable)
design of plug-in connection	male
mechanical data	
material	Stainless steel V2A
color	Silver
tightening torque / of the screw for securing the equipment / maximum	3 N·m
mounting distance	
 relating to metal surfaces / recommended / minimum 	0 m
ambient conditions	
ambient temperature	
 during operation 	-25 +70 °C
 during storage 	-40 +85 °C
during transport	-40 +85 °C
protection class IP	IP67
shock acceleration	500 m/s ²
vibrational acceleration	200 m/s ²
design, dimensions and weights	
depth	40 mm
diameter	18 mm
net weight	40 g
fastening method	2 x stainless steel nuts M18 x 1
wire length / of antenna wire	3 m
standards, specifications, approvals	
certificate of suitability	CE, cULus
certificate of suitability	
• IECEx	Yes
for IECEx / as marking	the ATEX approval of the connected reader applies
reference code	
 according to IEC 81346-2 	TF
 according to IEC 81346-2:2019 	TFB
accessories	

accessories	Included: 6GT2391-0AH30 (antenna cable)
further information / internet-Links	
Internet-Link	
to web page: selection aid TIA Selection Tool	https://support.industry.siemens.com/cs/ww/en/view/67384964
 to website: Industrial communication 	http://www.siemens.com/ident/rfid
to website: Industry Mall	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

• to website: Industry Online Support

https://support.industry.siemens.com

11/3/2021 🖸

• to website: Image database

• to website: CAx-Download-Manager