



SAFETY DATA SHEET
5L SUPER PROFESSIONAL CABINET GLASS WASH C3
 Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 5L SUPER PROFESSIONAL CABINET GLASS WASH C3
Product number 800-232-1120 C3
Container size 5L

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Machine glass washing detergent.
Uses advised against DO NOT use for hand glass washing.

1.3. Details of the supplier of the safety data sheet

Supplier Mirius™
 A Coventry Group Company
 Woodhams Road
 Siskin Drive
 Coventry
 CV3 4FX
 Tel: +44 (0) 02476 639 739
 Fax: +44 (0) 02476 639 717
 Email: sales@mirius.com

Contact person For content of safety data sheet:, sds@mirius.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1865407333 (Strictly for emergencies only: incidents involving damage to human health and/or the environment)

National emergency telephone number In case of a medical emergency following exposure to a chemical call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318
Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) C;R34.

2.2. Label elements

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

Pictogram



Signal word	Danger
Hazard statements	H314 Causes severe skin burns and eye damage.
Precautionary statements	P260 Do not breathe vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with local regulations.
Contains	TETRASODIUM ETHYLENE DIAMINE TETRAACETATE, SODIUM HYDROXIDE
Detergent labelling	5 - < 15% EDTA and salts thereof
Supplementary precautionary statements	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P321 Specific treatment (see medical advice on this label). P405 Store locked up.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE 5-10%		
CAS number: 64-02-8	EC number: 200-573-9	REACH registration number: 01-2119486762-27-XXXX
Classification	Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H302	Xn;R22 Xi;R41	
Acute Tox. 4 - H332		
Eye Dam. 1 - H318		
SODIUM HYDROXIDE 1-5%		
CAS number: 1310-73-2	EC number: 215-185-5	REACH registration number: 01-2119457892-27-XXXX
Classification	Classification (67/548/EEC or 1999/45/EC)	
Met. Corr. 1 - H290	C;R35	
Skin Corr. 1A - H314		
Eye Dam. 1 - H318		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

4.1. Description of first aid measures

General information	Get medical attention immediately. Provide eyewash station and safety shower.
Inhalation	Remove affected person from source of contamination. Keep affected person warm and at rest. Get medical attention immediately. For breathing difficulties, oxygen may be necessary.
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Chemical burns must be treated by a physician. Get medical attention immediately.
Inhalation	Severe irritation of nose and throat. May cause an asthma-like shortness of breath.
Ingestion	This product is corrosive. Small amounts may cause serious damage. May cause chemical burns in mouth, oesophagus and stomach.
Skin contact	May cause serious chemical burns to the skin.
Eye contact	This product is corrosive. A single exposure may cause the following adverse effects: Severe irritation, burning, tearing and blurred vision. Prolonged contact causes serious eye and tissue damage. Corneal damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. Remove contaminated clothing immediately and wash skin with soap and water.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire. Foam, carbon dioxide or dry powder.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	In contact with some metals can generate hydrogen gas, which can form explosive mixtures with air. Avoid contact with the following materials: Aluminium. Zinc. Avoid contact with water. May generate heat.
-------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Control run-off water by containing and keeping it out of sewers and watercourses.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid or minimise the creation of any environmental contamination. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Do not touch or walk into spilled material. Stop leak if safe to do so. Small Spillages: Flush away spillage with plenty of water. Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For waste disposal, see Section 13. See Section 11 for additional information on health hazards. See Section 1 for emergency contact information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Avoid the formation of mists. Provide adequate ventilation. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Never add water directly to this product as it may cause a vigorous reaction or boiling. Always dilute by carefully pouring the product into water.

Advice on general occupational hygiene Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Eye wash facilities and emergency shower must be available when handling this product. Wash promptly with soap and water if skin becomes contaminated. Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a well-ventilated place. Store away from the following materials: Acids. Oxidising materials.

Storage class Corrosive storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

SODIUM HYDROXIDE

Short-term exposure limit (15-minute): WEL 2 mg/m³

WEL = Workplace Exposure Limit

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE (CAS: 64-02-8)

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

DNEL	General population - Oral; Long term systemic effects: 25 mg/kg/day General population - Inhalation; Long term local effects: 0.6 mg/m ³ General population - Inhalation; Short term local effects: 1.2 mg/m ³ Workers - Inhalation; Long term local effects: 1.5 mg/m ³ Workers - Inhalation; Short term local effects: 3 mg/m ³
PNEC	- Fresh water; 2.2 mg/l - Marine water; 0.22 mg/l - Intermittent release; 1.2 mg/l - STP; 43 mg/l - Soil; 0.72 mg/kg

SODIUM HYDROXIDE (CAS: 1310-73-2)

DNEL	Industry - Inhalation; Long term local effects: 1.0 mg/m ³ Consumer - Inhalation; Long term local effects: 1.0 mg/m ³
-------------	--

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

Wear protective gloves. Neoprene. Nitrile rubber. Polyethylene. Polyvinyl chloride (PVC).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station and safety shower. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Particulate filter, type P2. Particulate filters should comply with European Standard EN143.

Environmental exposure controls

Avoid releasing into the environment. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	No characteristic odour.
pH	pH (concentrated solution): >13
Relative density	1.100 TYPICALLY @ 20°C
Solubility(ies)	Soluble in water.
Explosive under the influence of a flame	Not considered to be explosive.

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

Comments Information given is applicable to the product as supplied.

9.2. Other information

Other information Not relevant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Reactions with the following materials may generate heat: Water. Strong acids. In contact with some metals can generate hydrogen gas, which can form explosive mixtures with air. Avoid contact with the following materials: Aluminium. Zinc. Tin.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions The following materials may react violently with the product: Chlorohydrocarbons. Acids. Reactions with the following materials may generate heat: Water.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Acids. Ammonia. Chlorinated hydrocarbons. Aluminium. Tin. Zinc.

10.6. Hazardous decomposition products

Hazardous decomposition products Hydrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available. Information given is based on data of the components and of similar products.

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - oral

Notes (oral LD₅₀) Estimated value. Calculation method. Based on available data the classification criteria are not met.

ATE oral (mg/kg) 25,872.09

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Causes severe burns. Calculation method.

Serious eye damage/irritation

Serious eye damage/irritation Corrosivity to eyes is assumed.

Respiratory sensitisation

Respiratory sensitisation Not sensitising. Based on available data the classification criteria are not met.

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Does not contain any substances known to be mutagenic.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

General information Corrosive to skin and eyes.

Inhalation Spray/mists may cause respiratory tract irritation. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

Ingestion May cause burns in mucous membranes, throat, oesophagus and stomach.

Skin contact May cause serious chemical burns to the skin. Repeated exposure may cause skin dryness or cracking.

Eye contact Causes burns. A single exposure may cause the following adverse effects: Corneal damage. Contact with concentrated chemical may very rapidly cause severe eye damage, possibly loss of sight.

Toxicological information on ingredients.

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 1,780.0

Species Rat

ATE oral (mg/kg) 1,780.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 4.14

Species Rat

ATE inhalation (dusts/mists mg/l) 4.14

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Animal data Erythema/eschar score: No erythema (0). REACH dossier information.

Serious eye damage/irritation

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

Serious eye damage/irritation	REACH dossier information. Causes eye irritation. Dose: 1.3, 24-72 hours, Rabbit
<u>Skin sensitisation</u>	
Skin sensitisation	REACH dossier information. Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Negative.
Genotoxicity - in vivo	Negative.
<u>Carcinogenicity</u>	
Carcinogenicity	There is no evidence that the product can cause cancer.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	REACH dossier information. This substance has no evidence of toxicity to reproduction.

SODIUM HYDROXIDE

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	2,000.0
Species	Rat
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	2,000.1
Species	Rabbit
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Burning pain and severe corrosive skin damage.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Causes serious eye damage.
<u>Skin sensitisation</u>	
Skin sensitisation	Not sensitising.

SECTION 12: Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

Ecological information on ingredients.

SODIUM HYDROXIDE

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Toxicity The product may affect the acidity (pH) of water which may have hazardous effects on aquatic organisms.

Acute aquatic toxicity

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

Acute toxicity - aquatic plants May cause long lasting harmful effects to aquatic life.

Acute toxicity - terrestrial Can cause damage to vegetation.

Ecological information on ingredients.

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, (very soft water 34-62mg/l) 96 hours: 41 mg/l, Lepomis macrochirus (Bluegill)
LC₅₀, (medium hard water 136-204mg/l) 96 hours: 159 mg/l, Lepomis macrochirus (Bluegill)
LC₅₀, (very hard water 473-598mg/l) 96 hours: 532 mg/l, Lepomis macrochirus (Bluegill)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 140 mg/l, Daphnia magna

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOEC, 35 days: 25.7 mg/l, Brachydanio rerio (Zebra Fish)

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 25 mg/l, Daphnia magna

SODIUM HYDROXIDE

Acute aquatic toxicity

Acute toxicity - fish REACH dossier information.
LC₅₀, 96 hours: < 180 mg/l, Freshwater fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 40.4 mg/l, Freshwater invertebrates

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not available.

Chronic toxicity - aquatic invertebrates Not available.

12.2. Persistence and degradability

Persistence and degradability Degrades very slowly in nature.

Ecological information on ingredients.

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

Biodegradation REACH dossier information.
Water and sediment - Degradation 55%: 20 days

SODIUM HYDROXIDE

Persistence and degradability The product contains inorganic substances which are not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

Ecological information on ingredients.

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

Bioaccumulative potential BCF: ~ 1.8, Lepomis macrochirus (Bluegill)

SODIUM HYDROXIDE

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is water-soluble and may spread in water systems.

Ecological information on ingredients.

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

Henry's law constant REACH dossier information. 1.19E-18 Pa m³/mol @ 25°C

SODIUM HYDROXIDE

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

SODIUM HYDROXIDE

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Ecological information on ingredients.

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

Other adverse effects None known.

SODIUM HYDROXIDE

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered.

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

Disposal methods The packaging must be empty (drop-free when inverted). Wash with plenty of water. Dispose of waste via a licensed waste disposal contractor. Reuse or recycle products wherever possible.

Waste class EWC Code: 06 02 04

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1719
UN No. (IMDG)	1719
UN No. (ICAO)	1719
UN No. (ADN)	1719

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE)
Proper shipping name (IMDG)	CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE)
Proper shipping name (ICAO)	CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE)
Proper shipping name (ADN)	CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE)

14.3. Transport hazard class(es)

ADR/RID class	8
ADR/RID classification code	C5
ADR/RID label	8
IMDG class	8
ICAO class/division	8
ADN class	8

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-A, S-B
ADR transport category	2

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

Emergency Action Code 2R

Hazard Identification Number 80
(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). Environmental Protection Act 1990. The Hazardous Waste Regulations 2005. EH40/2005 Workplace exposure limits. The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) 1907/2006, Waste Material Code 91/689/EEC Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with amendments. Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. Technical Guidance WM2: Hazardous Waste. COSHH Essentials. ECHA Guidance on the Application of the CLP Criteria. ECHA Guidance on the compilation of safety data sheets.

15.2. Chemical safety assessment

A Chemical Safety Assessment (CSA) has been completed for Sodium hydroxide.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet EWC European Waste Catalogue
STOT RE = Specific target organ toxicity-repeated exposure
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.
PNEC: Predicted No Effect Concentration.
DNEL: Derived No Effect Level.

General information Only trained personnel should use this material.

5L SUPER PROFESSIONAL CABINET GLASS WASH C3

Revision comments	New revision number applied to comply with Commission Regulation (EU) No 2015/830 Of 28 May 2015' NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	06/07/2018
Revision	2
Supersedes date	14/06/2017
SDS number	20622
Risk phrases in full	R22 Harmful if swallowed. R34 Causes burns. R35 Causes severe burns. R41 Risk of serious damage to eyes.
Hazard statements in full	H290 May be corrosive to metals. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H332 Harmful if inhaled.