## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Böhmer Leuchten

Supplier's address: -

## Model identifier: 44325

## Type of light source:

| Lighting technology used:     | LED        | Non-directional or directional: | NDLS |  |  |  |
|-------------------------------|------------|---------------------------------|------|--|--|--|
| Light source cap-type         | matt cover |                                 |      |  |  |  |
| (or other electric interface) |            |                                 |      |  |  |  |
| Mains or non-mains:           | NMLS       | Connected light source (CLS):   | Nein |  |  |  |
| Colour-tuneable light source: | Nein       | Envelope:                       | -    |  |  |  |
| High luminance light source:  | Nein       |                                 |      |  |  |  |
| Anti-glare shield:            | Nein       | Dimmable:                       | No   |  |  |  |
| Product parameters            |            |                                 |      |  |  |  |

|                                      |  | i iouuci para                |   |              |  |  |
|--------------------------------------|--|------------------------------|---|--------------|--|--|
| Parameter                            |  | Value                        | Parameter   | Value        |  |  |
| General product parameters:          |  |                              |   |              |  |  |
| 0,                                   | mption in on-<br>100 h), rounded<br>st integer                             | 24                           | Energy efficiency<br>class  | F            |  |  |
| indicating if it r<br>in a sphere (3 | us flux (фuse),<br>efers to the flux<br>60º), in a wide<br>n a narrow cone | 1 950 in Wide<br>cone (120°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 3 000        |  |  |
| On-mode p<br>expressed in W          | oower (P <sub>on</sub> ),  | 24,0                         | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,50         |  |  |
| for CLS, expre                       | idby power (P <sub>net</sub> )<br>ssed in W and<br>second decimal          | -                            | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 80           |  |  |
| Outer                                | Height   | -                            | Spectral power  | See image    |  |  |
| dimensions                           | Width  | 380                          | distribution in the   | in last page |  |  |
| without                              | Depth  | 50                           | -   |              |  |  |
|                                      |  |                              |   |              |  |  |

| separate                                   |      | range 250 nm to 800   |      |  |  |  |
|--|------|-----------------------|------|--|--|--|
| control gear,                              |      | nm, at full-load      |      |  |  |  |
| lighting                                   |      |                       |      |  |  |  |
| control parts                              |      |                       |      |  |  |  |
| and non-                                   |      |                       |      |  |  |  |
| lighting                                   |      |                       |      |  |  |  |
| control parts,                             |      |                       |      |  |  |  |
| if any                                     |      |                       |      |  |  |  |
| (millimetre)                               |      |                       |      |  |  |  |
| Claim of equivalent power <sup>(a)</sup>   | -    | lf yes, equivalent    | -    |  |  |  |
|  |      | power (W)             |      |  |  |  |
|  |      | Chromaticity          | -    |  |  |  |
|  |      | coordinates (x and y) | -    |  |  |  |
| Parameters for LED and OLED light sources: |      |                       |      |  |  |  |
| R9 colour rendering index value            | 80   | Survival factor       | 0,95 |  |  |  |
| the lumen maintenance factor               | 0,95 |                       |      |  |  |  |
| (a),                                       |      |                       |      |  |  |  |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;