

## Thread former, HSSE-AlCrN M ISO 2X (6HX) 0° 371 similar to C

For universal use up to 1300 N/mm<sup>2</sup>

**ATORN**<sup>®</sup>



### Application

For manufacturing metric threads in through and blind holes on CNC or conventional machines **with oil lubrication** in **steel, stainless steel and non-ferrous metals up to a strength of 1300 N/mm<sup>2</sup>**.

### Advantage

- Innovative mould geometry ensures very high dimensional accuracy and process reliability.
- High-quality, torsion-resistant HSSE cutting material and surface finish for very high service life requirements.

Application	Steel (N/mm <sup>2</sup> )			Stainless steel		Alu		Brass		Bronze		Plas-tics	Graphite G(C)FK	GG(G) GjMW	Titan-alloy	Nickel-alloy	Super-alloy	Hard mat.	
	<700	<1000	<1300	marten.	austen.	short	long	short	long	short	long							<55 HRC	<65 HRC
	30	25	10	10	7	26	38	20	30	18	25								

<b>Art. No.</b>	<b>13394 580</b>
<b>Surface</b>	AlCrN
<b>Lead angle shape</b>	C
<b>Thread type</b>	Metric thread
<b>Thread type x nominal diameter</b>	M8
<b>Pitch</b>	1.25 mm
<b>Cutting material</b>	HSSE
<b>Core hole diameter</b>	7.4 mm
<b>Length</b>	90 mm
<b>Hole type</b>	Clearance/blind hole ≤ 3xD
<b>Shaft diameter</b>	8 mm
<b>Shank square</b>	6.2 mm
<b>Coolant supply</b>	External
<b>Tolerance of screw taps</b>	ISO 2X (6HX)
<b>Application type/machine type</b>	CNC, Conventional
<b>Cutting speed (steel 1000) suitability</b>	1
<b>Cutting speed (steel 1300) suitability</b>	1
<b>Overall stainless steel suitability</b>	1
<b>fitness not iron total</b>	2
<b>Cutting speed (cast) suitability</b>	3
<b>fitness Titan/Nickel/Super total</b>	3
<b>Cutting speed (hard 65) suitability</b>	3
<b>DIN</b>	Similar to 371

### EAN-Code

4050293040883