



Main

Range of product	Multi 9
Product or component type	OC contact
Device short name	OF
Signal contacts composition	1 C/O
Line Rated Current	3 A 415 V AC - 50/60 Hz 6 A ≤ 240 V AC - 50/60 Hz
[Uc] control circuit voltage	240...415 V AC 50/60 Hz 24...130 V DC
9 mm pitches	1

Complementary

Range compatibility	Multi 9 C60 C60BPR Multi 9 C60H-DC C60H-DC Multi 9 C60 C60SP Multi 9 C60 C60BP
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Mounting mode	Fixed
Mounting support	DIN rail
Height	3.35 in (85 mm)
Maximum Width	0.35 in (9 mm)
Depth	2.89 in (73.5 mm)
Net Weight	0.07 lb(US) (0.03 kg)
Connections - terminals	Clamp terminal bottom) 1 0.00 in ² (2.5 mm ²) AWG 14) - rigid Clamp terminal bottom) 2 0.00 in ² (1.5 mm ²) AWG 16) - rigid
Wire stripping length	9 mm for bottom connection
Tightening torque	8.85 lbf.in (1 N.m) bottom

Environment

Standards	EN/IEC 60947-5-1 EN 62019-2
Product certifications	CSA UR UL CCC PCT
Ambient air temperature for operation	-13...122 °F (-25...50 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)

Ordering and shipping details

Category	00948 - M9 GEN 2 CB UL1077 / IEC
Discount Schedule	DE2
GTIN	00785901759263
Nbr. of units in pkg.	1
Package weight(Lbs)	0.08 lb(US) (0.04 kg)
Returnability	Yes
Country of origin	BE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.83 in (2.1 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	3.74 in (9.5 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	18.06 oz (512 g)
Package 2 Height	3.94 in (10 cm)
Package 2 width	3.54 in (9 cm)
Package 2 Length	10.63 in (27 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Weight	11.23 lb(US) (5.095 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.