TOPJOB® S Double-Deck Terminal Blocks 1 (1.5) mm² 2000 Series

0.14 ... 1 (1.5) mm² AWG 24 ... 16 500 V/6 kV/3 2 600 V, 10 A 94 I_N 13.5 A (16 A)


Terminal block width 3.5 mm / 0.138 in. 5 ... 11 mm / 0.39 in. €


0.14 ... 1 (1.5) mm² AWG 24 ... 16 500 V/6 kV/3 2 600 V, 10 A 74 I_N 13.5 A (16 A)


Terminal block width 3.5 mm / 0.138 in. 9 ... 11 mm / 0.39 in.

0.14 ... 1 (1.5) mm² AWG 24 ... 16 500 V/6 kV/3 2 600 V, 10 A 94 I_N 13.5 A (16 A)


Terminal block width 3.5 mm / 0.138 in. 5 ... 11 mm / 0.39 in. €








	Item No.	Pack. Unit		Item No.	Pack. Unit		Item No.	Pack. Unit	
Through/through terminal block,			Through/through terminal block,			Ground conductor/through terminal block,			
with marker carrier,			with marker carrier,			with marker carrier,			
gray housing			blue housing			gray housing			
◯ L/L	2000-2231	50	N/N	2000-2234	50	PE/N	2000-2247	50	
○ N/L	2000-2232	50				PE/L	2000-2257	50	
◯ L/N	2000-2233	50							
Through/through terminal block,			Through/through terminal block,			Ground conductor/through terminal block,			
without marker carrier,			without marker carrier,			without marker carrier,			
gray housing			blue housing			gray housing			
◯ L/L	2000-2201	50	N/N	2000-2204	50	PE/N	2000-2217	50	
○ N/L	2000-2202	50				PE/L	2000-2227	50	
O L/N	2000-2203	50							







	Item No.	Pack. Unit		Item No.	Pack. Unit		Item No.	Pack. Unit
4-conductor through terminal block,			4-conductor through terminal block,			4-conductor ground terminal block,		
with marker ca	rrier, internal commoning, co	onductor entry	with marker carrier, internal commoning, conductor entry			with marker carrier, internal commoning,		
position colored in violet,			position colored in violet,			green-yellow housing		
gray housing			blue housing					
○ L	2000-2238	50	O N	2000-2239	50	O PE	2000-2237	50
4-conductor through terminal block,			4-conductor through terminal block,			4-conductor ground terminal block,		
without marker	carrier, internal commoning	, conductor	without marker carrier, internal commoning, conductor			without marker carrier, internal commoning,		
entry position colored in violet,			entry position colored in violet,			green-yellow housing		
gray housing			blue housing					
□ L	2000-2208	50	O N	2000-2209	50	PE PE	2000-2207	50