


4mm Retractable Shroud Stackable Test Leads



DESCRIPTION

A range of 4mm Retractable Shroud Stackable Test Leads.

DISTINCTIVE FEATURES

- Available in black, red, yellow, green & blue colours
- Stackable connectors
- · Retractable shrouds
- CATII rated

APPLICATIONS

Suitable for a wide range of test applications, including connection of Test and Electrical equipment where safety, shrouded test connectors and multiple connections are required.













GENERAL SPECIFICATION

Series	Test Leads	
Туре	4mm Stackable test leads with retractable shroud	
Quantity	1	
Wire size/type	1.0mm²	



ELECTRICAL SPECIFICATION

Rated Voltage	600V
Rated Voltage	1500V (leads only)
Rated Current	Max 19A (leads only)
Contact Resistance	≤0.005Ω
Insulating Resistance	≥500ΜΩ



MATERIALS

Material (Contact)	Nickel plated brass
Material (Insulator)	PE
Material (Cable Insulation)	PVC



ENVIRONMENTAL/OPERATING SPECIFICATION

Flame Retardancy (cable & plugs)	U1581L VW-1
Operating Temperature (cable & plugs)	-10°C~80°C
RoHS	Yes




CERTIFICATION AND STANDARDS

Rated Voltage	CATII
---------------	-------



DIMENSIONS/DRAWINGS

Units	mm - unless stated otherwise
Length (cable)	1000mm
Length (overall)	1112mm
Length (stackable plug)	56mm
Cable gauge	17 AWG
Cable outside diameter	3.9mm
Weight	38g







PART NUMBER TABLE

Part Number	Insulator or Body Colour	Cable Colour	EAN	UNSPSC	Country of Origin
52-4596	Black	Black	5053556006083	39121435	China
52-4597	Red	Red	5053556006090	39121435	China
52-4598	Blue	Blue	5053556006106	39121435	China
52-4599	Yellow	Yellow	5053556006113	39121435	China
52-4600	Green	Green	5053556006120	39121435	China



Important Notice: This data sheet and its contents (the "Information") belong to Rapid Electronics Limited or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Rapid Electronics Limited assumes no responsibility for its accuracy or completeness, any error in or onission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Rapid Electronics Limited were aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict Rapid Electronics Limited's liability for death or personal injury resulting from its negligence.

Datasheet 586596_v1.0 (06/22)Page 3 of 3